# STREAMLINING DIGITAL MODELING AND BUILDING INFORMATION MODELLING (BIM) USES FOR THE OIL AND GAS PROJECTS

Cen-Ying Lee<sup>1,\*</sup>, Heap-Yih Chong<sup>1</sup>, Xiangyu Wang<sup>1</sup>
<sup>1</sup>School of Built Environment, Curtin University, Australia

\* cenying.lee@ postgrad.curtin.edu.au

#### **Abstract**

The oil and gas industry is a technology-driven industry. Over the last two (2) decades, it has heavily made use of digital modeling and associated technologies (DMAT) to enhance its commercial capability. Meanwhile, the Building Information Modelling (BIM) has grown at an exponential rate in the built environment sector. It is not only a digital representation of physical and functional characteristics of a facility, but it has also made an impact on the management processes of building project lifecycle. It is apparent that there are many similarities between BIM and DMAT usability in the aspect of physical modeling and functionality. The aim of this study is to streamline the usage of both DMAT and BIM whilst discovering valuable practices for performance improvement in the oil and gas projects. To achieve this, twenty-eight (28) BIM guidelines, eighty-three (83) DMAT academic publications and one hundred and one (101) DMAT vendor case studies were selected for review. The findings uncover (a) thirty-eight (38) BIM uses; (b) thirty-two (32) DMAT uses and; (c) thirty-six (36) both DMAT and BIM uses. The synergy between DMAT and BIM uses would render insightful references into managing efficient oil and gas's projects. It also helps project stakeholders to recognise future investment or potential development areas of BIM and DMAT uses in their projects.

Keywords: Digital Modeling, Associated Technologies, Building Information Modeling, Streamline, Oil and Gas

### 1. Introduction

Oil and gas sector contributes significantly to more than half of humanity's primary energy supply (BHP, 2015). However, out of the total of 365 oil and gas megaprojects in the world, 73% of projects were reported schedule delays and 64% of projects experienced cost overruns (EY, 2014). One of the main factors contributed to project failures is management, contracting and project delivery strategies (Credit Suisse, 2014). It is envisaged that the technological prowess and advances should be incorporated into future oil and gas projects to embrace new thinking for performance improvement (Reid and Cann, 2016).

In the built environment sector, Building Information Modelling (BIM) is recognised as an emerging digital tool which enables information sharing of resources for a facility to form a reliable source for decision making throughout the project lifecycle (National BIM Standards, 2015). It is not only the digital representations of physical and characteristics of a facility but it is also a philosophy which transforms the way facilities are designed and managed by encouraging collaboration of all stakeholders' roles in a project (Azhar, 2011). Due to its potential values and benefits, BIM has been strongly advocated by many governments in the world. For instance, the Singapore government has mandated the implementation of BIM since 2013 (Teo et. al., 2015). The UK government also required all centrally procured public projects deploy BIM at level 2 by 2016 (HM Government, 2014). In Australia, the Federal Government's Infrastructure, Transport and Cities Parliamentary Committee has recommended that all major government infrastructure projects (over the value of \$50 million) to implement BIM (Infrastructure Australia, 2016). BIM is commonly viewed in 3D, but the model includes information used by other building analysis applications, such as energy simulation, computational fluid dynamics (CFD), day lighting, cost estimating and building code checking (GSA, 2015). BIM adoption goes beyond design and construction, and it extends to the project management and facility

management as the files of BIM can be extracted and exchanged to support decision making in connection with a facility.

On the other hand, it has been a few decades that the oil and gas projects deployed DMAT to enhance data management and collaboration process among the interdisciplinary team. DMAT refers to 3D geometric models and/or geometric bedding models and it's associated technologies which are usually adopted by the oil and gas industry to realise its facility. DMAT in the context of this study represents a simple 3D geometric model which contains very little intelligence or it may consist of high-level intelligence that is usually organised as a prototype of the facility to perform various functions. For exploration and production, geometry 3D bedding modeling such as the reservoir modeling has been developed to improve estimation of reserves (Abdideh and Bargahi, 2012); prediction of future production (Beeson et. al., 2014); and evaluating alternative reservoir management scenarios (Tavallali and Karimi, 2016). For design, construction and operation of the oil and gas facilities, plant lifecycle management (PLM) were deployed to allow multi-disciplinary teams like piping, electrical, mechanical, civil, structural and architectural design work concurrently under a collaboration platform (Intergraph, 2016). Information extracted from a plant model can be used for procurement such as material management, strategic sourcing and contract management (Xue, 2015). Apart from geometry bedding modelling and PLM, other DMAT uses which also have similar functionality and physical attributes with the BIM such as a unified information model of oil loading station was created in Samara Oblast, Russia, which used a mobile device on site for accessing information of model and project planning (Bentley, 2015, p. 123). Both BIM and DMAT are observed to have common attributes such as both technologies create 3D virtual models and they could interoperate with other technologies to achieve the project outcomes.

Some BIM uses could be potentially applied in the oil and gas industry to enhance their project performance. BIM and Augmented Realty (AR) could be used for project visualisation as it allows designers and owners to gain an immersive and interactive experience (Wang et al., 2014) prior to oil and gas plant fabrication and installation. BIM and Firefly Algorithm (FA) could be integrated to automatically

develop an optimal tower crane layout plan (Wang et al., 2015) for the oil and gas project construction. Besides, BIM and Light Detection and Ranging (LiDAR) could be developed to provide real-time information for on-site quality control (Wang et al., 2015a). Mechanical, plumbing and electrical (MEP) are essential facility elements that formed a majority components of the oil and gas plant fabrication and installation. A practical BIM framework which integrated the MEP layout from preliminary design to construction stage was formulated to resolve the design and constructability issues (Wang et al., 2016). To improve defect management practices in the oil and gas projects, BIM information could be linked with defects data effectively by converting it to RDF format and implementing SPARQL queries (Lee et al., 2016). Past oil and gas projects failed to deliver their desired outcomes due to many re-works, design errors, inefficiency in construction and life cycle performance failures. A total constraint management (TCM) framework which incorporated BIM and other related technologies was developed to improve oil and gas construction workflow and productivity (Wang et al., 2016a).

There were reviews on the BIM uses in building and infrastructure projects but none of the studies were carried out to identify BIM uses in the oil and gas industry. Twenty-four (24) industrial reports and more than forty (40) case studies in academic publications were collected and assessed to determine current BIM uses and the emerging BIM applications among the building, airports, bridges and roadworks (Shou et al., 2014). The BIM and its associated technologies applications of the road projects in Australia and China were also be compared to analyse the differences in the cultural and managerial practices between the projects in two countries (Chong et al., 2016).

Infrastructure Australia (2016) asserted that the best practices require a focus on the harmonisation which means the practices and standards have to be aligned to reduce duplication and improve delivery. To identify potential BIM applications and its associated technologies for improving oil and gas project performance, it is important to streamline both DMAT and BIM uses. The synergy between DMAT and BIM uses could create a better understanding for the oil and gas industry to plan, design, develop and operate its facilities whilst distinguish valuable key process areas be brought into the oil and gas industry for performance improvement.

To achieve the aim, this paper outlines three objectives as follows: - (1) to synthesis BIM uses from BIM guidelines; (2) to determine DMAT uses in the oil and gas industry; and (3) to streamline BIM and DMAT uses for the oil and gas industry.

### 2. BIM and DMAT Uses

The term "uses" is originated to classify the BIM uses so that project participants who will deploy the BIM in their projects could communicate and collaborate the specific value of a particular BIM application prior to the BIM implementation. The motivation behind the identification of BIM uses is that there is no common language existed for project participants to precisely communicate the purposes among each other for implementing BIM (Kreider, 2013).

While some BIM guidelines expressed the term of BIM uses as "BIM deliverables", other guidelines used the term of "BIM applications" which in fact carry the similar meaning as the former. If we view all these terms as the synonyms of BIM uses, there are many BIM guidelines that outlined the BIM uses. However, only a few guidelines that defined the meaning of the BIM uses clearly. NATSPEC (2016) asserted that BIM uses should not link intrinsically to project phases but they should be selected to support project goals at the beginning of the project and be planned how to deploy during different project phases. The nature of BIM technology allows different stakeholders use the BIM in multiple ways depending on the specific needs they may have (NYCDDC, 2012). Hence, BIM uses could be defined as the BIM tools that are deployed to coordinate the specific purposes for realising the project objectives.

A similar rationale is applied to the DMAT uses as the ultimate goal of the oil and gas owners and/or operators are to realise a facility which would be delivered on time, within their budgets, safely, complied with the strict environmental regulations, satisfied other stakeholders and to optimise their production during operation. To achieve project outcomes, BIM and DMAT uses should be classified based on the purposes and objectives as in table 1.

Table 1: BIM and DMAT Uses Purposes

BIM use purpose	BIM use objective	Synonyms
Gather	It captures current status of a facility, quantifies	administer, collect, manage, acquire,
	the amount of a facility element, monitors the	quantity take-off, observe, measure,
	information and qualifies the status of facility	follow, track, identify
	elements.	
Generate	It prescribes the need for and specify facility	create, author, model, program, specify,
	elements, arrange the placement of facility	configure, lay out, locate, place, scale,
	elements and determines the magnitude and size	engineer
	of facility elements.	
Analyse	It coordinates the relationship of facility	examine, evaluate, detect, avoid, simulate,
	elements, forecasts the future performance of the	predict, check, confirm
	facility and validates the accuracy of the facility	
	information.	
Communicate	It allows visualisation of a facility, transforms	exchange, review, translate, draft,
	the information to be received by another	annotate, detail, specify, submit, schedule,
	process, draws a symbolic representation of the	report
	facility and documents the specification of the	
	facility elements.	
Realise	It facilitates the facility information for	implement, perform, execute,
	fabrication, assembles the separate facility	manufacture, prefabricate, manipulate,
	elements, controls the operation of executing	direct
	equipment and regulates the operation of a	
	facility element.	

Note: This table is extracted from the National BIM Standard (2015)

# 3. Review Methodology

Figure 1 demonstrated a five-stage review framework which was used in this study.

Figure 1 Five-Stage Review Framework

#### **Step 1: Problem Identification** There is an inconsistent language of BIM and DMAT uses between the Built Environment sector and the oil and gas industry. Hence, there is a need to bridge the semantic gap of BIM and DMAT uses between these two industries to provide a better understanding for the oil and gas industry to communicate precise purpose and context of implementing these technologies for improving project performance. Step 2 Search for Evidence Stages Sources Evidences BIM guidelines Keyword: BIM guidelines Stage 1 Select Literature Search DMAT uses: Select • Years: 2012-2016 · Peer-reviewed Journal • Keyword: 3D model oil gas Articles and Conference Papers • DMAT Vendor Case Studies Stage 2 • BIM guidelines Select Discussed the BIM uses Literature Filtration • DMAT academic Select Discussed the DMAT uses publications (Peer-Reviewed) • DMT Vendor case studies

	Step 3 Evaluate Data (Fine	dings)
Sources	Actions	Evidences
BIM guidelines	Synthesis and Tabulate	BIM Uses
<ul> <li>DMAT academic publications</li> <li>DMAT Vendor case studies</li> </ul>	Synthesis and Tabulate	DMAT Uses

Sources	Actions	Evidences
BIM Uses	Streamline and Tabulate	Streamlined BIM and DMAT Uses
<ul> <li>DMAT Uses</li> </ul>		<ul> <li>Distinguished DMAT Uses</li> </ul>

Step 5 Conclusion and Recommendations

The first step involved in this study was problem identification. Next, to identify the solution to the problem, an intensive literature search was carried out. The Google search engine was deployed to identify BIM guidelines. BIM guidelines were selected if they stated or sufficiently discussed BIM usability and its purpose. Figure 2 demonstrates the numbers of the BIM guidelines from 2012 to 2016 and also country by publications used in this study. The highest numbers of BIM

guidelines were in the year of 2012. This may due to the rapid growth and use of BIM in the industry. The highest number of publications was recorded by the United States which consisted eighteen (18) articles. The significant high number of BIM guidelines in this country mainly due to the greater adoption and use of BIM in the country.




Figure 2: Years, numbers and country by publication of BIM guidelines

On the other hand, the usability of DMAT was determined through; (1) peer-reviewed journal articles and conference papers; and (2) DMAT vendor case studies. The Google scholar was used to identify the academic publication whereas the Google search engine was deployed to identify DMAT objective by DMAT vendors. Some of the common DMAT vendors selected in this study were as follows:-


Table 2: List of Common DMAT vendors selected

Disciplines	DMAT Vendors								
Exploration and Production	Schlumberger, Landmark, Paradigm, Petex								
Design, Procure and Construct	Bentley, Autodesk, Synchro, AVEVA (formerly known as PDMS and Tribon), Intergraph, Tekla, Aspentech								

Commissioning, Operation, and	WinPCS, AVEVA, Intergraph, Bentley, Autodesk, Schlumberger
Maintenance	

All data was retrieved from 2012 to 2016 to identify the recent trends of DMAT uses in the oil and gas industry. The keyword deployed for searching the academic publications were "3D model oil gas". The data was filtered through the elimination process. The academic publications and vendor case studies were selected if they sufficiently discussed the DMAT purpose. Figure 3 shows the numbers and years of academic publications and DMAT vendor case studies adopted in this study.

Figure 3: Years and numbers of DMAT Academic Publications and Vendor Case
Studies



There were total eighty-three (83) DMAT academic publications and one hundred and one (101) DMAT vendor case studies selected in the study. Both types of sources projected a very dissimilar trend. Most of the DMAT academic publications that used in the study were in the year 2013 and 2014 which accounted for 24 and 23 respectively whereas the majority of the DMAT vendor case studies adopted in the study was in the year of 2015, which recorded forty-nine (49) number.

The data gained from the BIM guidelines, academic publications and vendor case studies were tabulated for analysis. To synthesise the BIM and DMAT uses, the term adopted in the references which had a similar connotation and similar definition were classified into the same theme. The BIM and DMAT uses extracted from the BIM guidelines, DMAT academic publications and DMAT vendor case studies were presented based on the project lifecycle as outlined in Table 4 to ease the understanding of the readers. The data of BIM and DMAT uses were also presented according to the purpose as outlined in Table 1.

Table 4 Project Lifecycle Used In the Study

No.	cycle stated in	Activity model of the process plant life-cycle (ISO 15926)  gas industry life this study are phases described to references.	Oil and Gas Industry Life Cycle Tabulate in This Study (DMAT)	Description	Project Life Cycle Tabulate in This Study (BIM)	Description
1	Exploration	-	Exploration	It includes seismic surveys to look for potential oil or/and gas sources (Darko 2014).	-	-
2	Appraisal	Conceptual Process Design, Conceptual Engineering Design (Front End)	Appraisal	This phase determines the projects should proceed or terminate based on the results of the potential of oil or/and gas reserves (Darko 2014). It also involves feasibility study, site planning and front-end engineering design (FEED) for production, transportation and processing oil and gas facilities projects.	Plan	This phase is the most important phase to determine the feasibility of the project. It includes site analysis, determination of the project location, conceptual design and preparation of initial estimate.
3	Development	-	Development	Wells and reservoirs are developed.  Production operation	-	

	1	<u> </u>				
				and maintenance strategies are also		
				established (Darko		
				2014).		
3a	_	Detailed	Design	It includes detailed	Design	This phase
Ja		Process Design,	Design	engineering design.	Design	includes the
		Detailed		engineering design.		schematic design
		Engineering				of a facility to the
		Design				selection of
		Design				contractor (Chong,
						2016a).
3b	_	Procure and	Procure	It describes the	Procure	ŕ
30	-	Procure and Control	Procure		Procure	Same as the
		Equipment,		ordering, purchasing and control of		description of the oil and gas
		Material and		materials, equipment		oil and gas industry
		Services,		and services from		procurement
		Suppliers and		fabricators and		stage.
		Fabricators		suppliers.		suige.
3c		Construct Plant,	Construct	This stage involves	Construct	Same as the
36		Pre-	Construct	construction and	Construct	description of the
		Commission		fabrication of oil and		oil and gas
		Commission		gas facilities.		industry
				gus ruemties.		construction stage.
4	Production	Commission	Production,	Oil or/and gas reserves	Operate	This stage
·	and Operation	Plant, Operate	Operate and	are being extracted and	and	includes the
	and operation	Plant, Maintain	Maintain	transported for	Maintain	operation and
		Plant and		processing/ exported.		maintenance of a
		Equipment		It also involves		facility (Chong
		1.1		commission, operates,		and Wang, 2016).
				modifications and		<i>G,</i> ,
				maintains plant and		
				equipment during the		
				life of oil and gas		
				facilities.		
5	Abandonment	Decommission,	Demolition	This phase involves	-	This section is not
		Demolition		well abandonment,		available as none
		Plant and		dismantle the plants		of this phase
		Restore Site		and restore the site to		mentioned in the
				its original condition.		BIM guidelines.
<u> </u>	I .	I				

Thereafter, a streamlining process was conducted. If a BIM and DMAT use share the common function, they would be aligned with the same theme which represents its use. For the DMAT uses which did not have common functions as the BIM uses, it would be classified as the distinguished DMAT uses. Throughout the streamlining process, the BIM uses which were not commonly applied in the oil

and gas projects could also be identified. The results were discussed. Limitations, conclusions and recommendations were then formulated and concluded at the end of this review.

# 4. Findings

# 4.1 BIM Uses

Table 5 demonstrates thirty-eight (38) BIM uses which were extracted from twenty-eight (28) BIM guidelines.

# Table 5 List of BIM Uses

No.	BIM Uses/ Description		Proj	ject Pl	hases		References (BIM Guidelines)	BIM	Use
		Plan	Design	Procure	Construct	Onerate		Purposes	
1	Existing Conditions Modeling  A process in which a 3D model of the existing conditions for a site, facilities on a site or a specific area within a facility is developed (PSU, 2011). It includes modelling of the existing ground surface of the structures, the adjacent area and the infrastructure for project master planning, existing facilities and assets, existing spaces, building components and equipment, geotechnical elements and horizontal construction such as roadways, raised bridges, walkways and transportation is developed so that the total environment of the facilities can be modeled effectively (MPA, 2015).	x	x		x	x	(BCA, 2013); (COD, 2011); (COSA, 2011): (CRC, 2009): (DOA/DSF, 2012); (FMS, 2012); (GISFIC, 2013); (GTFM, 2013); (Harvard, 2016); (HKCIC, 2015); (IU, 2015); (LACCD, 2016); (MPA, 2015); (NATSPEC, 2016); (NHBA, 2012); (NRC, 2014); (NYCSCA, 2014); (NYDDC, 2012); (OFCC, 2012); (PSU, 2011); (SDCCD, 2012); (Statsbygg, 2013); (TPA, 2016); (USACE, 2012)	Gather; Gene	rate
2.	Site Analysis  A process in which BIM or GIS tools are used to evaluate the site location to determine :(1) an appropriate location for a future project (NYCDDC, 2012); and (2) analyse the volumes, location (placement, orientation) of the facility(s) on site (Statsbygg, 2013).	х					(BCA, 2013); (COD, 2011); (HKCIC, 2015); (NATSPEC, 2016); (NRC, 2014); (NYDDC, 2012); (OFCC, 2012); (PSU, 2011); (TPA, 2016); (USACE, 2012)	Analyse	
3	Cost Estimation  A process in which BIM can be used to establish accurate cost estimate and cost effects of changes made to the design can be traced from the BIM which enables designers to curb excessive cost overruns due to project modifications (NYCDDC, 2012). It includes cost planning, quantity take-off and cost tracking.	х	х	х	х	х	(AGC, 2009); (BCA, 2013); (CFM, 2010); (COD, 2011); (COSA, 2011); (CRC, 2009); (DOA/DSF, 2012); (HKCIC, 2015); (IU, 2015); (LACCD, 2016); (MPA, 2015); (NATSPEC, 2016); (NRC, 2014); (NYSCA, 2014); (NYDDC, 2012); (PSU, 2011); (SDCCD, 2012); (SEC, 2013); (TPA, 2016); (USACE, 2012); (GTFM, 2016)	Gather; Gen Analyse	ierate,
a	Cost analysis (5D)/Cost and Schedule Forecast  A process in which a 5D BIM is deployed to link the cost data to 4D BIM (NATSPEC, 2016) for cost analysis and generating cash flow forecast report.	х	х	х	х	х	(AGC, 2009); (CFM, 2010); (CRC, 2009); (LACCD, 2016); (NATSPEC, 2016); (NRC, 2014); (SEC, 2013); (Statsbygg, 2013); (TPA, 2016); (USACE, 2012)	Analyse, Communicate	e
4	Phase Planning (4D Modeling)/ Scheduling  A process in which phased occupancy is planned effectively through utilisation of 4D model so that a project team can visualise and communicate for a better understanding of project milestones and construction plans (PSU, 2011). It involves early project phasing to allow for comparison of different strategies, detail phasing to sequence multi-trade installation and scheduling for project control (Harvard, 2016).	х	х	х	х		(AGC, 2009); (BCA, 2013); (CFM, 2010); (COD, 2011); (COSA, 2011); (CRC, 2009); (DOA/DSF, 2012); (GISFIC, 2013); (GTFM, 2016); (Harvard, 2016); (HKCIC, 2015); (LACCD, 2016); (MPA, 2015); (NATSPEC, 2016); (NRC, 2014); (NYCSCA, 2014); (NYDDC, 2012); (PSU, 2011); (SDCCD, 2012); (SEC, 2013); (Statsbygg, 2013); (TPA, 2016); (USACE, 2012)	Communicate	ð
5	Programming/ Are and Space Program Validation  A process in which area and program information is extracted from BIM to assess the space design as the design develops. It allows tracking rentable area, gross area and usable area (Harvard, 2016.).	х					(BCA, 2013); (CFM, 2010); (COD, 2011); (COSA, 2011); (CRC, 2009); (DOA/DSF, 2012); (FMS, 2012); (GISFIC, 2013); (GTFM, 2016); (Harvard, 2016); (HKCIC, 2015); (IU, 2015); (LACCD, 2016); (MPA, 2015); (NATSPEC, 2016); (NYCSCA, 2014); (NYDDC, 2012); (OFCC, 2012); (PSU, 2011); (SDCCD, 2012); (Statsbygg, 2013); (TPA, 2016); (UCASE, 2012)	Generate	
6	Design Authoring  A process in which authoring tools are deployed by multi-disciplinary teams to add richness of information to a facility (HKCIC, 2015).	х	х	х	Х		(CFM, 2010); (COD, 2011); (COSA, 2011); (FMS, 2012); (Harvard, 2016); (HKCIC, 2015); (LACCD, 2016); (NRC, 2014); (NYDDC, 2012); (PSU, 2011); (SDCCD, 2012); (Statsbygg, 2013); (TPA, 2016); (USACE, 2012)	Generate	
7	Design Reviews and Constructability Reviews  A process in which a 3D model is viewed by stakeholders through different forms of presentations to provide their feedbacks for multiple design aspects validation (PSU, 2011.). It involves design selection from various options provided by the BIM, design communication through visualisation and digital mock-ups (Harvard, 2016).	х	х				(AECUK, 2015); (AGC, 2009); (BCA, 2013); (CFM, 2010); (COD, 2011); (COSA, 2011); (DOA/DSF, 2011); (FMS, 2012); (GISFIC, 2013); (Harvard, 2016); (HKCIC, 2015); (LACCD, 2016); (MPA, 2015); (NATSPEC, 2016); (NRC, 2014); (NYCSCA,	Communicate	è

					2014) (ALVERDO 2012) (OFGO 2012) (PGH 2011) (PDGOD 2012) (G I	
					2014); (NYDDC, 2012); (OFCC, 2012); (PSU, 2011); (SDCCD, 2012); (Statsbygg,	
					2013); (TPA, 2016); (USACE, 2012)	
8	Modeling	х	х		(AECUK, 2015); (AGC, 2009); (CFM, 2010); (BCA, 2013); (COSA, 2011); (COD,	Generate
	Each facility system shall be organised as a separate model linked to a common origin point for efficient coordination purposes. (LACCD,				2011); (CRC, 2009); (FMS, 2012); (GISFIC, 2013); (GTFM, 2016); (IU, 2015);	
	$2016). It includes an architectural {\it model which consists of material and spatial design, structural, MEPF, interiors and any other common}$				(LACCD, 2016); (MPA, 2015); (NATSPEC, 2016); (NHBA, 2012); (NYSCA, 2014);	
	models for building a facility.				(OFCC, 2012); (SDCCD, 2012); (Statsbygg, 2013);	
a	Civil Engineering/ Infrastructure Model	х	х		(CFM, 2010); (COD, 2011); (COSA, 2011); (CRC, 2009); (FMS, 2012); (GTFM,	Generate
	A process in which civil engineering model is created to represent civil engineering or infrastructure elements which shall distinguish				2016); (HKCIC, 2015); (LACCD, 2016); (OFCC, 2012); (SDCCD, 2012); (Statsbygg,	
	with building models. The civil engineering or infrastructure elements may include site topography model, landscaping elements and site				2013)	
	utilities models (FMS, 2012) with the aids of associated technologies such as GIS (Statsbygg, 2013, LiDAR and etc. Bridge, main road,					
	highway, railway and tunnel models (NRC, 2014) are the examples of civil engineering models.					
b	Equipment Modeling and Maintenance Clearance Space Modeling	х	х	 $\dashv$	(FMS, 2012); (MPA, 2015); (SDCCD, 2012)	Generate
	A process in which equipment models are created to indicate its location, sizes and details (FMS, 2012). It also includes modeling for					
	maintenance space and consideration of typical maintenance cycles, replacement paths continuity of operations so that adjacent					
	equipment can be serviced at the same time (MPA, 2015).					
					TO A AND COTTAL AND COOR AND COTTAL AND CO.	
с	Energy Modeling	х	х		(BCA, 2013); (CFM, 2010); (COD, 2011); (GTFM, 2015); (Harvard, 2016); (IU, 2015);	Generate
	Due to the timing of analysis and potential model clean-up, energy analysis is often performed separately from the BIM (Harvard, 2016).				(MPA, 2015); (NHBA, 2012); (OFCC, 2012)	
	It streamlines the simulation process quickly with minimal data from existing building conditions to develop an energy analysis (MPA,					
	2015).					
9	Design Analysis/ Engineering Analysis		х		(BCA, 2013); (COD, 2011); (CRC, 2009); (DOA/DSF, 2009); (GISFIC, 2013);	Analyse
	A process in which the models are simulated with typical analysis software or used for structural analysis, lighting analysis, fire safety				(Harvard, 2016); (HKCIC, 2015); (MPA, 2015); (NATSPEC, 2016); (NYDDC, 2012);	
	analysis etc.				(PSU, 2011); (SDCCD, 2012); (Statsbygg, 2013); (TPA, 2013); (USACE, 2012)	
a	Energy Analysis		х		(BCA, 2013); (CFM, 2010); (COD, 2011); (CRC, 2009); (DOA/DSF 2009); (GISFIC,	Analyse
	A process in which energy simulation and lifecycle cost are analysed with the information extracted from BIM (CFM, 2010). The scope				2013); (GTFM, 2016); (Harvard, 2016); (HKCIC, 2015); (IU, 2015); (LACCD, 2016);	
	includes renewable energy analysis (SDCCD, 2012).				(MPA, 2015); (NATSPEC, 2016); (NHBA, 2012); (PSU, 2011); (SDCCD, 2012);	
					(Statsbygg, 2013); (TPA, 2016); (USACE, 2012)	
b	Accessibility Analysis		х		(Statsbygg, 2013)	Analyse
	A process of using colours, lighting conditions, acoustics and etc. which are not so straightforward to check as geometry requirements to					
	$assess\ the\ practicability\ and\ accessibility\ for\ all\ people\ which\ include\ people\ with\ disabilities\ (Statsbygg,\ 2013).$					
c	Proximity Analysis		х		(Statsbygg, 2013)	Analyse
	A process of deploying BIM to conduct proximity analysis for determining the appropriate travel distance between areas to another area					
	(Statsbygg, 2013).					
d	Security and Circulation Analysis		х	1	(Statsbygg, 2013)	Analyse
	A process in which a BIM is simulated with a security and circulation analysis software to analyse the circulation areas where the building					
	has define security zones (Statsbygg, 2013).					
e	Acoustics Analysis		х		(CRC, 2009); (Harvard, 2016); (Statsbygg, 2013)	Analyse
	A process in which BIM is simulated with an acoustical analysis tool to perform room acoustical analysis and sound insulation calculations					
	(Statsbygg, 2013).					
f	Mechanical Analysis/ Virtual Testing and Balancing/ System Analysis/ Building Disposal Analysis		х	$\dashv$	x (BCA, 2013); (CFM, 2010); (COD, 2011); (COSA, 2011); (CRC, 2009); (Harvard,	Analyse
	A process to compare a facility performance with the design specifications. It includes assessments of how a mechanical system operates,				2016); (HKCIC, 2015); (MPA, 2015); (NATSPEC, 2016); (NRC, 2014); (NYDDC,	
	how much energy a project uses, conducting lighting analysis, solar gain analysis and airflow analysis using CFD (HKCIC, 2015).				2012); (PSU, 2011); (Statsbygg, 2013); (TPA, 2016); (USACE, 2012)	
		1				

σ	Sustainability Evaluation/Environmental Analysis/ Environmental Hazardous Products Analysis	v	v	v	v	v	(BCA, 2013); (COD, 2011); (CRC, 2009); (DOA/DSF, 2012); (GISFIC, 2013);	Analyse
5	A process in which models are used to simulate and validate facility properties such as thermal performance, energy use, structural	^	^	^	Λ.	Λ.	(GTFM, 2016); (Harvard, 2016); (HKCIC, 2015); (LACCD, 2016); (NATSPEC, 2016);	Analyse
	calculations, acoustics, heat flows, Life Cycle Costing (LCC), Life Cycle Analysis (LCA) and environmental sustainability (CRC, 2009)						(NYDDC, 2012); (PSU, 2011); (Statsbygg, 2013); (TPA, 2016); (USACE, 2012)	
	based on the requirement of standard sustainability assessment.						(N1DDC, 2012), (F30, 2011), (Statsbygg, 2013), (FFA, 2010), (USACE, 2012)	
							GDV AND GOD AND GWGG AND G GD AND GD AND GD	
1	Civil Engineering Analysis		х				(CFM, 2010); (COD, 2011); (HKCIC, 2015); (LACCD, 2016); (SDCCD, 2012); (NRC,	Analyse
	A process in which the models of civil engineering elements can be analysed with the aids GPS, LiDAR and any other forms of technologies						2014)	
	such as for the hydraulic design of water supply, sewerage, storm water drainage systems (HKCIC, 2015), surface analysis and traffic							
	simulation (NRC, 2014).							
	Signal Sighting		x				(NRC, 2014)	Analyse
	A process in which BIM can be deployed to design and test the new signaling proposals before fixing (NRC, 2014).							
	Code Validation/Building Code Analysis/ Model Checking Program/ Compliance Checking/ Design Validation		х				(AECUK, 2015); (CFM, 200); (COD, 2011); (CRC, 2009); (GTFM, 2016); (Harvard,	Analyse
	A process in which code validation software is utilised to check the model parameters against project specific codes (PSU, 2011). Apart						2016); (IU, 2015); (LACCD, 2016); (MPA, 2015); (NATSPEC, 2016); (NRC, 2014);	
	from compliance validation, it includes prescription and functionality validation (NRC, 2014).						(NYDDC, 2012); (OFCC, 2012); (PSU, 2011); (Statsbygg, 2013); (TPA, 2016);	
							(USACE, 2012)	
.0	Design Coordination / 3D Coordination/ Interference Management/Clash Avoidance and Detection		х				(ARC, 2009); (BCA, 2013); (CFM, 2010); (COD, 2011); (COSA, 2011); (CRC, 2009);	Analyse
	A process in which clash detection software is deployed to analyse the BIM for physical interferences between building systems and						(DOA/DSF, 2012); (FMS, 2012); (GISFIC, 2013);(GTFM, 2016); (Harvard, 2016);	
	components, clashes are manually sorted and reported (Harvard, 2016). Automated clash detection analysis for drainage and utility						(HKCIC, 2015); (IU, 2016); (LACCD, 2016); (MPA, 2015); NATSPEC, 2016); (NRC,	
	networks is made possible with BIM tools (NRC, 2014).						2014); (NYCSA, 2014); (NYDDC, 2012); (OFCC, 2012); (PSU, 2011); (SDCCD,	
							2012); (SEC, 2013); (Statsbygg, 2013); (TPA, 2016); (USACE, 2012)	
1	Design Documents/ Drawing Generation		х				(BCA, 2013); (CFM, 2010); (COD, 2011); (CRC, 2009); (Harvard, 2016); (LACCD,	Communicate
	A process in which design documents such as schematic, design development, construction and shop drawings are extracted directly from		^				2016); (PSU, 2011); (SDCCD, 2012)	Communicate
	the BIM repositories or object libraries (PSU, 2011).						2010), (150, 2011), (55005), 2012)	
2	Digital Fabrication	-		x	x		(AGC, 2009); (BCA, 2013); (CFM, 200); (COD, 2011); (CRC, 2009); (GTFM, 2016);	Realise
2				Х	Х			Realise
	A process in which geometry from the BIM is extracted for shop drawings and can be sent to computer numerical control equipment for						(Harvard, 2016); (HKCIC, 2015); (LACCD, 2016); (MPA, 2015); (NATSPEC, 2016);	
	prefabrication and erected efficiently on site (Harvard, 2016).						(NRC, 2014); (NYCSCA, 2014); (NYDDC, 2012); (OFCC, 2012); (PSU, 2011); (TPA,	
							2016); (USACE, 2012)	
13	Subcontractor/ Trade Coordination			Х	X		(AGC, 2009); (CFM, 2010); (COD, 2011); (NATSPEC, 2016); NYCSCA, 2014)	Realise
	A process in which a coordinated model is deployed for the contractor to coordinate with the subcontractors for review the design, optimise							
	scheduling and field installation prior to installation (NATSPEC, 2016).							
4	Material Management			x	X		(NRC, 2014)	Gather; Generate
	A process in BIM is used to support multiple-user access, receive, track and control all project deliverables such as prefabrication							
	components and other small construction support materials to ensure the materials deliver on schedule and meet the quality expectations							
	(NRC, 2014).							
5	Equipment Management			х	Х		(NRC, 2014)	Gather; Generate
	A process in which BIM is deployed to support construction equipment management such as scheduling the downtime to fit project							
	workload, produce maintenance schedules, complete service history and work arrangement (NRC, 2014).							
6	Site Utilisation Planning/ Site and Logistic Planning				х		(AGC, 2009); (COD, 2011); (CRC, 2009); (Harvard, 2016); (HKCIC, 2015);	Communicate
	A process in which detailed logistic objects are modeled in the BIM (Harvard, 2016) and link to construction schedule (4D) (HKCIC,						(NATSPEC, 2016); (NRC, 2014); (PSU, 2011); (TPA, 2016); (USACE, 2012)	
	2015) for permanent and temporary facilities on site (PSU, 2011).							
7	3D Control and Planning (Digital Layout)/ In field Construction Layout	+			х		(COD, 2011)); (Harvard, 2016); (HKCIC, 2015); (MPA, 2015); (NRC, 2014); (PSU,	Communicate
	A process in which layout points are taken from the BIM and loaded into robotic total stations for layout. Conversely, layout points are						2011); (USACE, 2012)	
	captured in the field during construction and round-tripped back to the model for proactive quality control (MPA, 2015).						/, (,42/	
	captured in the fred daring construction and tound-ripped oder to the model for productive quality control (MTA, 2013).	1						

10	Lift Planning	1		- 1	v		(NATSPEC, 2016)	Communicate
10					А		(NA 15FEC, 2010)	Communicate
	A process in which lift plan models are created through collaboration between the structure engineers and experienced site personnel							
	such as lift supervisor to communicate the lift plan for execution (NATSPEC, 2016).							
19	Safety/Safety Planning/Site Safety Review				х		(GISFIC, 2013); (Harvard, 2016); (MPA, 2015); (NRC, 2014); (TPA, 2016)	Communicate
	A process in which BIM is deployed to develop safety plans for communication on site and off site such as information for emergency							
	routes of public safety measures can be extracted from the BIM (Harvard, 2016) and BIM-based orientation can be used to provide safety							
	training (MPA, 2015).							
20	Construction System Design				Х		(COD, 2011); (NATSPEC, 2016); (NYDDC, 2012); (PSU, 2011); (TPA, 2016);	Generate;
	A process in which complex building systems such as modular construction components, formwork and scaffolding can be modeled to						(USACE, 2012)	Communicate
	improve planning, construction productivity and safety (NATSPEC, 2016).							
21	Progress Tracking						(NRC, 2014)	Gather
21					х		(NRC, 2014)	Gatner
	A process in which 4D BIM is integrated with laser scanning and mobile computing to assist project managers in assessing construction							
	progress effectively and make a timely decision if schedule delay appeared.							
22	Field and Management Tracking/ Quality Tracking and Reporting				х		(PSU, 2011); (Statsbygg, 2013); (USACE, 2012); (NRC, 2014)	Gather; Generate;
	A process in which Field Management software is used during the construction, commissioning, and handover process to manage, track,		l					Communicate
	task, and report on quality, safety, documents to the field, commissioning, and handover programs, connected to BIM for project							
	compliance (PSU,n.d.).							
23	Field Supplements				х		(AGC, 2009); (Harvard, 2016); (LACCD, 2016); (MPA, 2015); (SDCCD, 2012);	Communicate
	Data extracted from BIM can be used to support field supplements (Harvard, 2016) such as construction drawings and schedules, as-built						(Statsbygg, 2013); (TPA, 2016)	
	documents and sustainability certification documentation to be submitted as part of the project deliverables.							
24	Record Model/ As-built Model				х		(AECUK, 2015); (AGC, 2009); (BCA, 2013); (COD, 2011); (COSA 2011); (CRC,	Generate
	Record Modeling is the process used to depict an accurate representation of the physical conditions, environment, and assets of a facility.						2009); (GTFM, 2016); (Harvard, 2016); (HKCIC, 2015); (IU, 2015); (LACCD, 2016);	
							(MPA, 2015); (NATSPEC, 2016); (NRC, 2014); (NYDDC, 2012); (OFCC, 2012);	
	It is the culmination of all the BIM Modeling throughout the project, including linking Operation, Maintenance, and Asset data to the As-							
	Built model (created from the Design, Construction, 4D Coordination Models, and Subcontractor Fabrication Models) to deliver a record						(PSU, 2011); (SDCCD, 2012); (Statsbygg, 2013); (TPA, 2016); (USACE, 2012)	
	model to the owner or facility manager (PSU,2011).							
25	COBie/ Commissioning	х	х	х	Х	х	(CFM, 2010); (COD, 2011); (FMS, 2012); (GTFM, 2016); (IU, 2015); (LACCD, 2016);	Communicate;
	A systematic process of verifying that all building systems perform interactively according to the design intent and the owner's operational						(MPA, 2015); (NATSPEC, 2016); (NRC, 2014); (SDCCD, 2012); (SEC, 2013);	Realise
	needs (MPA, 2015).						(Statsbygg, 2013); (TPA, 2016); (USACE, 2012)	
26	Other FM information handover					х	(NATSPEC, 2016)	Communicate:
20	A process in which where the client and BIM Team determine that use of the COBie system is not appropriate for the project, other specific					Α.	(WIBI EC, 2010)	Realise
								Realise
	information required for facility management and the strategy for delivering it are purposed (NATSPEC, 2016).							
27	Operation and Maintenance Scheduling/ Preventive Maintenance Analysis			1		х	(BCA, 2013); (COD, 2011); (CRC, 2009); (HKCIC, 2015); (MPA, 2015); (NATSPEC,	Communicate
	$A \ process \ of \ record \ model/\ as\ -built \ model \ is \ deployed \ with \ building \ management \ system \ such \ as \ building \ automation \ system, \ computer \ is \ deployed \ with \ building \ management \ system \ such \ as \ building \ automation \ system, \ computer \ is \ deployed \ with \ building \ management \ system \ such \ as \ building \ automation \ system, \ computer \ is \ deployed \ with \ building \ management \ system \ such \ as \ building \ automation \ system, \ computer \ is \ deployed \ with \ building \ management \ system \ such \ as \ building \ automation \ system, \ computer \ is \ deployed \ with \ building \ management \ system \ such \ as \ building \ automation \ system, \ computer \ system \ such \ as \ building \ automation \ system, \ computer \ system \ s$		l				2016); (NRC, 2014); (PSU, 2011); (SDCCD, 2012); (Statsbygg, 2013); (TPA, 2016);	1
	maintenance management system to plan, manage and track operation and maintenance activities (PSU, 2011).						(USACE, 2012)	
28	Asset Management/Facility Management					х	(BCA, 2013); (COD, 2011); (CRC, 2009); (Harvard, 2016); (HKCIC, 2015); (MPA,	Gather; Generate;
	A process of bi-directionally linking an as-built model database to an organised building management system which can be used to						2015); (NATSPEC, 2016); (NRC, 2014); (NYDDC, 2012); (OFCC, 2012); (PSU,	Communicate
	maintain and operate a facility and its assets (HKCIC,2015). The assets include physical components, systems, surrounding environment						2011); (SDCCD, 2012); (Statsbygg, 2013); (TPA, 2016); (USACE, 2012)	
			l				2011), (3DCCD, 2012), (3tatsbygg, 2013), (1PA, 2010); (USACE, 2012)	1
	and equipment (NRC, 2014).							
29	Maintenance Training			I		x	(MPA, 2015)	Realise
	BIM can be used during commissioning, preoccupation, and post-occupation to train staff on asset location, maintenance access and							
	maintenance procedures. This information can be developed into a mobile accessible package (MPA, 2015).	1	ĺ					1

30	Space Management and Tracking			х	(BCA, 2013); (COD, 2011); (CRC, 2009); Harvard, 2016); (HKCIC, 2016); (MPA,	Gather;
	A process in which BIM may integrate with spatial tracking software to assess, manage and track the existing use space and associated				2015); (NATSPEC, 2016); (PSU, 2011); (SDCCD, 2012); (TPA, 2016); (USACE,	Communicate
	resources within a project (HKCIC, 2015)				2012)	
31	Disaster Planning/Contingency Planning Analysis			х	(COD, 2011); (CRC, 2009); (Harvard, 2016); (MPA, 2015); (NATSPEC, 2016); (NRC,	Generate; Analyse;
	A process in which BIM is used in conjunction with building management system for emergency response planning (NATSPEC, 2016).				2014); (PSU, 2011); (SDCCD, 2012); (Statsbygg, 2013); (TPA, 2016); (USACE, 2012)	Communicate
32	Assessment Models			х	(MPA, 2015)	Gather
	BIM can be used in the field for efficient data collection. Mobile software supporting BIM shall be considered by the assessment team					
	(MPA, 2015).					
33	Resiliency Modeling			х	(MPA, 2015)	Generate
	BIM can be used to create resiliency modeling particular for the projects where their assets and properties are located in areas subject					
	to environmental change (MPA, 2015).					
34	Road/Rail Management			х	(NRC, 2014)	Realise
	A process in which BIM is utilised to provide solutions to build and manage infrastructure models, analyse current working conditions of					
	infrastructure, plan for infrastructure improvement and future growth with the aids of various forms of technologies such as geospatial					1
	tracking and graphical representation of the networks (NRC, 2014).					
35	Transportation/Logistic Management System			х	(NRC, 2014)	Realise
	A process in which BIM transportation management tools are deployed to support entire transportation lifecycle ranging from creating					
	the least cost shipment plans and maximising loading capacity to streamlining freight financial administration for match- and auto-pay					
	or self-invoicing processes, as well as leverage end-to-end visibility for proactive monitoring and intelligent exception management for					
	whole distribution network (NRC, 2014).					
36	Traffic Volume Simulation			х	(NRC, 2014)	Analyse
	A process in which performance measures generated by BIM models and BIM visualization capabilities enable detailed operational					
	analyses of travel corridors in the area and assist in determining the potential effectiveness of transportation projects and access					
	management practices (NRC, 2014).					
37	GIS Asset Tracking			х	(NRC, 2014)	Gather
	A process in which BIM is deployed to monitor location and movement of objects in real time. Objects that can transmit their geographic					1
	location via Global Positioning Systems (GPS) or similar technologies can be dynamically tracked on a display map that can be shared					
	via the Internet or intranet (NRC, 2014).					
38	Water Mitigation and Planning			Х	(NRC, 2014)	Communicate
	A process in which BIM operation tools can be deployed to support appropriate legislation for flood plain zoning, implementation and					
	collection of data essential for the assessment of the community's flood risk (NRC, 2014).					
			_			

# $4.2\ DMAT$ Uses in the Oil and Gas Industry

Table 6 demonstrates thirty-two (32) DMAT uses extracted from a total of eighty-three (83) academic publications and one hundred and one (101) DMAT vendor case studies.

No.	DMAT Uses/ Description			Pr	oject I	Phase			References		
			Development		t/ Demolition	Academic Publications (most of the papers discussed the potential DMAT uses in the oil and gas projects or examined the DMAT uses in research, except for those with * indicates the DMAT uses were applied in the practice)	DMAT Vendor Case Studies	Purposes			
		Exploration	Appraisal /Plan	Design	Procure	Construct	Production, Operate	Abandonment/			
1	Geological Modeling  A process in which a 3D geological model is generated through repeated seismic surveys and predictions about its properties and structures (Abideh and Bargahi, 2012).	х	х				х		(Abideh and Bargahi, 2012); (Amanippor et al., 2013); (Besson et. al., 2014)*; (Cuba et. al., 2012); (Do Couto et.al., 2015); (Duran et al., 2013); (Fayemi and Di, 2016); (Lindsay et al., 2013); (Liu et al., 2012); (Tiruneh et al., 2013); (Turrini et al., 2014)*; (Zhu et al., 2013)	(Paradigm, 2013)	Generate
2	Reservoir Modeling  A process in which a geological model can be up-scaled to simulate with fluid behaviours under different sets of circumstances to identify the optimal production techniques. It is mainly used for charge risk assessments, locate new prospects, identify drilling targets, optimise completions and accelerate developments (Paradigm, 2016).	x	x				X		(Amoyedo et al., 2016); (Brigaud et al., 2014); (Bruns et al., 2013); (Cacace and Blocher, 205); (Dong et al., 2014); (Fegh et al., 2013); (Geiger et.al., 2012); (Glegola, 2013); (Kamali et al., 2013); (Katterbauer et al., 2014); (King et al., 2012)*; (Morongjiu-Porcu et al., 2016); (de Oliveira Miranda et al., 2015); (Naji and Khalil, 2012); (Norden et al., 2012); (Panfili et al., 2012); (Park and Datta-Gupta, 2013); (Senel et al., 2014)*; (Soleimani and Shokri, 2015); (Zeinalzadeh et al., 2015)	(Paradigm, 2016); (Paradigm, 2016b); (Paradigm, 2016c); Schlumberger, 2015b); (Schlumberger, 2016b)	Analyse
3	Data or Information Management A process in which a data or information management tool is deployed to collaborate multi-disciplinary teams in a common visualisation environment. It includes the deployment of other advanced IT tools such as big data (Perrons and Jensen, 2015), cloud computing (Perrons and Hems, 2013) and etc.	x	x	x	x	x	x	x	(Baaziz and Quoniam, 2013); (Chelmis et al., 2013); (Han et al., 2014); (He and Wang, 2015); (Kim et al., 2014); (Perrons and Hems, 2013); (Perrons and Jensen, 2015); (Popa and Cassidy, 2012)*; (Sawaryn et al., 2014); (Veyber et al., 2012); (Ward et al., 2014)*; (Zhu et al., 2015)	(Aveva, 2015a); (Aveva, 2015c); (Aveva, 2015, p.26-30); (Aveva, 2015, p.31-33); (Aveva, 2015, p.34-37); (Aveva, 2015, p.42-45); (Aveva, 2015, p.46-47); (Aveva, 2015, p.48-51); (Bentley, 2012, p.105); (Bentley, 2012, p.27); (Bentley, 2013, p.26); (Bentley, 2014, p.11 and p.73); (Bentley, 2014, p.110); (Bentley, 2014, p.115); (Bentley, 2015, p.105); (Bentley, 2015, p.122); (Bentley, 2015, p.122a); (Bentley, 2015, p.123a); (Bentley, 2015, p.124a); (Bentley, 2015, p.135); (Bentley, 2015, p.192); (Bentley, 2015, p.135); (Intergraph, 2013a); (Intergraph, 2013a); (Intergraph, 2016a); (Tekla, 2016a); (Tekla, 2016c); (Aspentech, 2015b)	Communicate
4	Well Planning A process in which a well is interpreted and it is assessed with well-planning software and reservoir modeling through various scenarios to quantify wellbore position and precision (Paradigm, 2016) for safe operation and at		x	x	х	х	х		(Chemali et al., 2014); (Jain et al., 2013); (Ask et al., 2015); (Odunowo et al., 2013); (Tavallali and Karimi, 2016); (Zhu et al., 2014)	(Landmark, 2016); (Paradigm, 2016a); (Schlumberger, 2013b); (Schlumberger, 2014); (Schlumberger, 2015a); (Schlumberger, 2016); (Schlumberger, 2016a);	Generate

	the lowest cost. A 3D drillable trajectory is designed			1				1			
	inside a subsurface model with well control simulation										
	software to understand and mitigate operational risks and										
	meet drilling regulations (Schlumberger, 2016). As										
	drilling operation is progress, reservoir model is updated										
	and coupled with simulation software to situate the good										
	structure and provide a more realistic drilling (Chemali										
	et al., 2014).										
5	Subsurface Model Review	х	Х	х			Х		- (Schlumberge	er, 2013); (Schlumberger, 2014a) Con	mmunication
	A process in which a 3D subsurface model and other										
	necessary data are reviewed by stakeholders through										
	different forms of presentations to assist in decision										
	making for well planning, drilling and production										
	optimisation (Schlumberger, 2013).										
6	Drilling Operation		х	х	х	х	х	1	(Downtown, 2015); (Iversen et al., 2013); (Nikolaou, 2013); (Tavallali (Schlumberge	er, 2012); (Schlumberger, 2013a) Rea	alise
	Drilling operations include utilisation of drilling								and Karimi, 2016);(Zhang and Zhang, 2012)	-	
	operations software and other services for drilling							1			
	engineers and the rig site to continuously monitor and										
	analyse drilling operations for drilling performance										
	optimisation, wellbore assurance, risk mitigation, and										
	operational efficiency (Schlumberger, 2016). The result of										
	the drilling data analysing data grid could be visualised										
	through 3D model (Zhang and Zhang, 2012).										
7	Existing Conditions Modeling		х	v		х	х	х	(Ward et al., 2014)*	Cot	ther, Generate
,				х							
a	As-Built Model		Х	х		х	х	х			ther, Generate
	A process in which an as-built model of an existing facility									reva, 2015, p.26-30); (Aveva, 2015, p.3-5); (Bentley, 2012, p. 109);	
	or a new built fabrication model is created through laser								(Bentley, 2014	4, p.98); (Intergraph, 2014a)	
	scanning technology (Aveva, 2015, p.16-19).										
8	Programming		х						(Ward et al., 2014)*	Gen	enerate
9	Phase Planning (4D Modeling)/ Scheduling		Х	Х		х	х	х	(Kim et. al., 2013); (Ward et al., 2014)*; (Zhou et al., 2015a) (Aveva, 2015	5,p.31-33); (Bentley, 2013,p.62); (Bentley, 2015,p.13); (Synchro, Con	mmunicate
									2014); (Synch	aro, 2015)	
10	Cost Estimation		х	х	х	х	х		- (Aspentech, 2	2015); (Asptentech, 2016) Gath	ther; Generate;
										Ana	nalyse
a	Quantity Extraction		х	х	х	х	х	1	(Ward et al., 2014)* (Aveva, 2015,	(p.13-15); (Aveva, 2015,p.26-30); (Aveva, 2015,p.34-37); (Bentley, Gatley)	ther
	It is a process in which a 3D model is used to extract							1	2012, p. 12	25); (Bentley, 2013,p.143); (Bentley, 2013,p.146); (Bentley,	
	quantity for cost estimation (Aveva, 2015, p.13-15).									Bentley, 2015, p. 103); (Bentley, 2015, p. 122); (Bentley, 2015, p. 192);	
								1		2013); (Intergraph, 2014a); (Intergraph, 2015); (Intergraph, 2015a);	
										2016a); (Tekla, 2016); (Tekla, 2016a)	
b	Cost Analysis (5D)/Cost and Schedule Forecast		х	х	х	х	х		(Wang et al., 2014a) -		alyse
	Design Authoring			<del> </del>	+	L_		+	(Ward et al., 2014)*; (Xie and Ma, 2015) (Autodesk, 20	012); (Autodesk, 2012a); (Aveva, 2015, p.48-51); (Bentley, 2012, Gen	enerate
1 11		1									
11	Design Authorning		х	х	х	х				tley, 2012, p.109); (Bentley, 2012, p.27); (Bentley, 2013, p.148-31); (Bentley, 2012, p.109); (Bentley, 2012, p.27); (Bentley, 2013, p.143);	nerate

		-						1	T	(Bentley, 2013, p.143); (Bentley, 2013,p.146); (Bentley, 2014,p.110); (Bentley,	
										2014, p.115);(Bentley, 2015, p.103); (Bentley, 2015, p.122); (Bentley, 2015,	
										p.122a); (Bentley, 2015, p.135); (Bentley, 2015, p.201); (Intergraph, 2013);	
										(Intergraph, 2013a); (Intergraph, 2014); (Intergraph, 2014a); (Intergraph, 2015a);	
										(Intergraph, 2016); (Tekla, 2016); (Tekla, 2016a); (Tekla, 2016c)	
12	Design Reviews		x	х					(Carvalho et al., 2012); (Kim et al., 2014); (Muley et al., 2014); (Ward et	(Aveva, 2015a); (Aveva, 2015,p.20-22); (Aveva, 2015,p.26-30); (Aveva,	Communicate
									al., 2014)*	2012,p.27); (Bentley, 2013, p. 20); (Bentley, 2014,p.110); (Bentley, 2014,p.115);	
										(Bentley, 2015,p.103); (Bentley, 2015,p.122); (Bentley, 2015,p.124); (Bentley,	
										2015,p.124a); (Bentley, 2015,p.135); (Bentley, 2015,p.201); (Intergraph, 2013);	
										(Intergraph, 2015a); (Intergraph, 2016a); (Tekla, 2016a)	
13	Modeling , Instrumentation and Diagram		х	х	х	х	х		(Li et al., 2013); (Savazzi et al., 2013); (Ward et al., 2014)*; (Zhou et al.,	(Autodesk, 2012); (Autodesk, 2012a); (Autodesk, 2013); (Autodesk, 2013a)	Generate
	It includes mechanical, structural, piping, equipment,								2015); (Norton et al., 2013); (Ma, 2014)*	(Aveva, 2015a); (Aveva, 2015c); (Aveva, 2015,p.10-12); (Aveva, 2015,p.13-15);	
	electrical, civil engineering and any other engineering									(Aveva, 2015,p.20-22); (Aveva, 2015,p.26-30); (Aveva, 2015,p.31-33); (Aveva,	
	modeling necessary for a facility. Concurrent design of									2015,p.34-37); (Aveva, 2015,p.3-5); (Aveva, 2015,p.46-47); (Aveva, 2015,p.48-	
	different disciplines may exist under a collaboration									51);(Bentley, 2012,p.105); (Bentley, 2012,p.125); (Bentley, 2012,p.27); (Bentley,	
	platform (Intergraph, 2016; Aveva, 2016). It also includes									2013,p.143); (Bentley, 2013,p.146); (Bentley, 2013,p.26); (Bentley, 2014,p.110);	
	the process of facilitating the instrumentation and									(Bentley, 2014,p.115); (Bentley, 2015,p.101); (Bentley, 2015,p.103); (Bentley,	
	diagram from various disciplines to support operational									2015,p.104); (Bentley, 2015,p.105);(Bentley 2015,p.105a); (Bentley,	
	tasks such as generating new as-built data, offer interface									2015,p.122); (Bentley, 2015,p.122a); (Bentley, 2015,p.123); (Bentley,	
	for calibration and SAP (one of the ERP providers) for									2015,p.124); (Bentley, 2015,p.124a); (Bentley, 2015,p.135); (Bentley, 2015,p.124b);	
	maintenance scheduling (Intergraph, 2016).All tools									2015,p.124), (Bentley, 2015,p.124a), (Bentley, 2015,p.135), (Bentley, 2015,p.192);(Intergraph, 2013); (Intergraph, 2013a); (Intergraph, 2014a);	
	discussed are necessary to support the changes made to									(Intergraph, 2015a); (Intergraph, 2016b); (Intergraph, 2016b); (Tekla, 2016c)	
										(Intergraph, 2013a); (Intergraph, 2016); (Intergraph, 20160); (Texia, 2016c)	
	ensure the information are always up-to-date.										
1.1											
14	Design Analysis/Engineering Analysis			Х					-	-	Analyse
a	Structural Analysis			X					(Ward et al., 2014)*	(Bentley, 2012,p.105); (Bentley, 2014,p.110); (Bentley, 2014,p.95); (Bentley,	Analyse
										2015,p.101); (Bentley, 2015,p.102); (Bentley, 2015,p.103); (Tekla, 2016)	
b	Offshore Structural Analysis								(Munoz-Garcia, 2013); (Paris and Cahay, 2015); (Ma, 2014)*	(Bentley, 2014,p.98); ; (Bentley, 2015,p.99); (Bentley, 2015,p.99a); (Bentley,	
	A process in which a structure is simulated with offshore									2015,p.101a); (Bentley, 2015,p.102); (Bentley, 2015,p.105); (Bentley,	
	system response such as hydrostatic, hydrodynamic,									2015,p.105a); (Bentley, 2015,p.106); (Bentley, 2015,p.106a); (Bentley,	
	mooring, and structural behaviour, for an example, blast									2015,p.107);	
	and explosion analysis to assess the offshore structural										
	integrity (Bentley, 2016).										
с	Spatial, Raceway and Cable System Analysis			х					-	(Aveva, 2015,p.31-33); (Aveva, 2015,p.34-37);(Bentley, 2015,p.103)	Analyse
	A 3D model can simulate with raceway and cable system										
	analysis software to identify the best path through										
	raceways using different segregation criteria and routing										
	methods for plant design (Bentley 2015, p.103).										
d	Process Analysis			X					(Pathak et al., 2013); (Walnum et al., 2013); (Kvesic et al. 2012)	(Aveva, 2015,p.34-37); (Intergraph, 2014); (Intergraph, 2015a); (Aspentech,	Analyse
	A 3D model can also be simulated with process analysis									2015a)	,
	software to address engineering challenges such as the									,	

	multiphase flow modeling, gas processing, refining and									
	LNG process (Aveva 2015, p.34-37).									
е	Material and/or Pipe Stress Analysis  A process in which material is analysed with simulation software. One of the examples is that the piping analysis was deployed to analyse the flexibility and stress of pipe. The model created could clearly indicate areas of concern via color-coded stress models and animated		х				(Hu et al	., 2015); (Munoz-Garcia, 2013)	(Aveva, 2015, p. 31-33); (Bentley, 2014,p.110); (Bentley, 2015, p.101); (Bentley, 2015, p. 103); (Bentley, 2015,p.105a); (Bentley, 2015,p.122a); (Bentley, 2015,p.123); (Bentley, 2015,p.124); (Bentley, 2015,p.135); (Intergraph, 2014); (Intergraph, 2014a); (Intergraph, 2015a)	Analyse
	displacements for any stress load case (Intergraph 2015a; Intergraph 2016; Intergraph 2016a).									
f	Acoustic Analysis		Х				-		(Bentley, 2015,p.123)	Analyse
g	Civil Engineering Analysis		х				(Ward et	. al., 2014)*	-	
h	Geospatial Analysis  The analysis is used to design and installation of the pipeline, field gathering stations, gas distribution manifolds, flow and trunklines, and water and gas reinjection facilities in El Merk (Intergraph, 2016b).	х	x			Х	-		(Intergraph, 2016b)	Analyse
i	Economic Evaluation  A process in which an economic model is embedded into process modeling to assess the viability of the capital, production, operation costs and any other associated costs arising from the planning until the demolition of the oil and gas facilities (Berk, 2011)s.	х	х	х	X	х	-		(Aspentech, 2015); (Asptentech, 2016)	Analyse
15	Code Validation/ Building Code Analysis/ Model Checking Program/ Compliance Checking/ Design Validation		х				-		*Almost most of the common design software has code compliance checking feature.	Analyse
16	Design Documents	x	х	x	x		(Ward et	al., 2014)*	(Aveva, 2015a); (Aveva, 2015c); (Aveva, 2015,p.10-12); (Aveva, 2015, p. 13-15); (Aveva, 2015, p. 34-37); (Aveva, 2015, p. 46-47); (Aveva, 2015, p. 48-51); (Bentley, 2012, p.125); (Bentley, 2012,p.27); (Bentley, 2013,p.143); (Bentley, 2013,p.146); (Bentley, 2014,p.140); (Bentley, 2015,p.101); (Bentley, 2015,p.102); (Bentley, 2015,p.103); (Bentley, 2015,p.104); (Bentley, 2015,p.105); (Bentley, 2015,p.122); (Bentley, 2015,p.122a); (Bentley, 2015,p.124a); (Bentley, 2015,p.135); (Bentley, 2015,p.124a); (Bentley, 2015,p.192); (Intergraph, 2013); (Intergraph, 2013a); (Intergraph, 2014a); (Intergraph, 2015a); (Intergraph, 2016); (Tekla, 2016a)	Communicate
17	Design Coordination / 3D Coordination/ Interference Management/Clash Avoidance and Detection		х	х	х		(Ward et	al., 2014)*	(Aveva, 2015a); (Aveva, 2015c); (Aveva, 2015,p.10-12); (Aveva, 2015,p.13-15); (Aveva, 2015,p.26-30); (Aveva, 2015,p.31-33); (Aveva, 2015,p.34-37); (Aveva, 2015,p.46-47); (Aveva, 2015,p.48-51); (Bentley, 2012,p.27); (Bentley, 2013,p.143); (Bentley, 2014,p.110); (Bentley, 2014,p.115); (Bentley, 2015,p.101); (Bentley, 2015,p.103); (Bentley, 2015,p.105a); (Bentley, 2015,p.122); (Bentley, 2015,p.122a);	Analyse

								2015,p.123); (Bentley, 2015,p.124); (Bentley, 2015,p.124a); (Bentley, 2015,p.135); (Intergraph, 2013); (Intergraph, 2014); (Intergraph, 2014a);	
								(Intergraph, 2015a); (Intergraph, 2016a); (Synchro, 2015); (Tekla, 2016); (Tekla, 2016c)	
18	Digital Fabrication		х	х			(Bedair, 2014); (Kul'ga and Men'shikov, 2015); (Ward et al., 2014)*	(Aveva, 2015a); (Aveva, 2015,p.10-12); (Aveva, 2015,p.20-22); (Aveva, 2015,p.26-30); (Aveva, 2015,p.34-37); (Intergraph, 2014a); (Tekla, 2016c)	Realise
19	Supplier and Subcontractor Management		х	х			-	(Aveva, 2015,p.26-30); (Aveva, 2015,p.34-37); (Aveva, 2015,p.48-51); (Intergraph, 2013); (Intergraph, 2015)	Gather; Generate
20	Material management		х	х	х		(Chi et al., 2015); (Trujens et al., 2014); (Xu et al., 2012)	(Aveva, 2015,p.23-25); (Aveva, 2015,p.26-30); (Aveva, 2015,p.34-37); (Aveva, 2015,p.48-51); (Aveva, 2015,p.40-41); (Bentley, 2013,p.62); (Intergraph, 2013); (Intergraph, 2015)	Gather; Generate
21	Equipment management		х	х			-	(Bentley, 2015,p.13)	Gather; Generate
22	Constructability Review  The real-time data integration on project development allows clients and other team members review construction progress from time to time (Bentley, 2015, p.13) to curb the schedule overrun.			x			(Carvalho et al., 2012); (Muley et al., 2014); Wang et al., 2014a)	(Bentley, 2015,p.13); (Synchro, 2015)	Communicate
23	Progress Tracking			х			(Wang et al., 2014b)	(Bentley, 2015,p.13)	Gather
24	Safety/ Safety Planning/Site Safety Review			х	х	х	(Albert et al., 2014); (Carvalho et al., 2012); (Chen et al., 2015); (Muley et al., 2014); (Norton, 2013); (Ward et al., 2014)*	(Bentley, 2015,p.13)	Communicate
25	Deconstruction Model  A deconstruction model is developed to assist in the analysis of the future deconstruction and reinstatement work. The model provides a central location for quantitative technical, environmental and cost data (Ward et al., 2014).				х	х	(Ward et al., 2014)*	-	Generate
26	Project Completion/ Certification Tracking System/ Commissioning It is a process in which structured database management system is used to track the engineering data from all disciplines. It provides a portal to import, sort, analyses and quality control the data before the engineering data is accepted and move into the database. It also reports the completion and certification of design changes (WinPCS, 2014).			x	X			(WinPCS, 2014); (WinPCS, 2014a); (WinPCS, 2014b)	Realise
27	Asset Management It involves asset management for onshore and offshore production, and downstream facility. It includes the scope for enterprise asset management (Aveva, 2015,p.40-41),				х		(Perrons and Richard, 2014); (Savazzi et al., 2013)	(Autodesk, 2012); (Autodesk, 2012a); (Autodesk, 2012a); (Aveva, 2015b); (Aveva, 2015,p.23-25); (Aveva, 2015,p.40-41); (Aveva, 2015, p.42-45); (Aveva, 2015,p.48-51); (Bentley, 2015,p.123a); (Bentley, 2015,p.135); (Intergraph, 2013a); (Schlumberger, 2015)	Gather; Generate; Communicate

	asset tracking (Autodesk, 2012, outage analysis (Autodesk, 2012a) and etc.						
a	Asset Visualisation			х	-	(Aveva, 2015b); (Aveva, 2015,p.26-30); (Aveva, 2015,p.31-33); (Aveva,	Communicate
	A process in which asset visualisation software is					2015,p.34-37); (Aveva, 2015,p.38-39); (Aveva, 2015,p.3-5); (Aveva, 2015,p.42-	
	deployed to allow team members to assess to detail and					45); (Aveva, 2015,p.48-51); (Aveva, 2015,p.6-9);(Bentley, 2015, p.123a)	
	up-to-date asset information for planning and controlling						
	of the facility (Aveva, 2015b).						
28	GIS Asset Tracking			х	-	(Autodesk, 2012); (Autodesk, 2012a)	Gather
29	Operation and Maintenance Scheduling			х	-	(Aveva, 2015,p.23-25); (Aveva, 2015,p.40-41)	Communicate
30	Disaster Planning			х	(Huang et al., 2016)	-	Generate, Analyse,
							Communicate
31	Operation or Maintenance Training			Х	(Colombo et al., 2014)	-	Realise
32	Production Management			х	(Allan et al., 2014); (Tavallali and Karimi, 2016); (Veyber et al., 2012);	(Landmark, 2012); (Petex, 2014)	Generate, Analyse,
					(Zhang and Zhang, 2012)		Communicate;
							Realise

# 5. Analysis and Discussion

By streamlining the table 5 and 6, there is a total of thirty-six (36) BIM and DMAT application (as shown in figure 4) which could be applied in the oil and gas industry.

Development Production, Operate and Appraisal/Plan Construct Maintain /Demolition Geological Modeling Reservoir Modeling Data/ Information Management Well Planning Subsurface Model Review **Drilling Operation** Economic Evaluation **Existing Conditions Modeling** Phase Planning (4D) Programming **Design Authoring** Modeling, Instumentation and Diagram Design and Engineering Analysis Offshore Structural Analysis Spatial, Cable and Raceway System Analysis Process Analysis Material and Pipe Stress Analysis Code Validation/ Compliance Checking Clash Detection/ Design Coordination Digital Fabrication Subcontractor Coordination/Management Constructability Review D Control and Planning (Digital ift Planning Streamlined BIM and DMAT Uses onstruction System Design Distinguished DMAT Uses As-Built Modeling/ Deconstruction Modeing Project Completion/Commissioning Assessment Models Resiliency Modeling ransportation/Logistic Management Production Management

Figure 4: Streamlined BIM and DMAT Uses for the Oil and Gas Industry

# 5.1 Exploration/Appraisal/Plan

Distinguished DMAT application shown in Figure 4 indicates that the practices which are commonly applied in the oil and gas industry but are rarely adopted in the built environment such as for the building and infrastructure projects. These include geological modeling, reservoir modeling, well planning, subsurface model review, drilling operation in the exploration and appraisal phases. These DMAT applications are distinguished from the BIM uses as it is not adequate to be adopted by the building and infrastructure projects due to the natural work process. These DMAT practices are mainly used in (1) exploration and production, and (2) process and production facility. Besides, sustainability evaluation is important to most of the building construction as it is the significant process informing the life-cycle cost of a building (Gourlis and Kovacic, 2016). However, for the oil and gas industry, evaluating the life cycle cost such as the capital, operation and production costs of the projects is the ultimate aim. Accurate economic models embedded in the process modeling is essential in assessing the viability of the oil and gas facilities such as for the LNG projects (Beck, 2011).

BIM and DMAT application in the oil and gas industry for data and information management become prominent. Some evidence of this application include hybrid cloud computing system (Bentley, 2012, p.27, p. 105) was deployed to accelerate communication across the project teams; for energy refinery in Alberta, Canada, an innovated information plant management system was established to gather, store and connect the facility's technical data, engineering resource planning information, and documents in a single, reliable system supporting the day-to-day operations and maintenance decisions; and the system encompasses electronic documentation management system, lifecycle server, SAP asset management system and plant design tools (Bentley, 2013, p. 26). Also, a master tag registry and engineering data warehouse were developed in Queensland Curtis LNG project to supply the commissioning team with critical information related to various systems, tags, and documents (Bentley, 2014, p.11 and p.73).

During the feasibility stage, existing conditions modeling and site analysis are required to model the existing site and the facilities in the surrounding for project master planning. However, these uses are not apparent in the oil and gas industry. Only a case study demonstrated the development of 3D model using BIM tool to

produce photomontages for inclusion in the environmental impact statement (Ward et. al., 2014). The majority of the existing conditions modeling are used for modeling the as-built oil and gas facilities. The adoption of the laser scanning for develop existing 3D models are gaining important in the oil and gas projects (Aveva, 2015a; Aveva, 2015, p.10-12; Aveva, 2015, p.13-15; Aveva, 2015, p.16-19; Aveva, 2015, p.26-30; Aveva, 2015, p.3-5; Bentley, 2012, p. 109; Bentley, 2014, p.98; Intergraph, 2014a) as there are getting more facilities required alterations and refurbishments. The laser scan data is easily imported into the design software and could be viewed effortlessly by the designers (Aveva, 2015, p.13-15). For process facility located in Bakersfield, California, laser scanning was utilised as verification tools at fabrication and construction process. Laser scan data in fabrication shop was imported to check against any deviations of the design model by informing decisions to reject or accept non-compliant piping components (Aveva, 2015, p. 16-19). Nevertheless, BIM uses such as cost estimating using model-based estimating software for 5D cost analysis and update the cost when there are changes made to the design (NYCDDC, 2012); and programming to track the design space (Harvard, 2016) which are important in planning a facility are not evident in the oil and gas projects.

# 5.2 Design

The practices of the oil and gas industry in modeling its facility is distinguished with that of the BIM in the built environment. The main focus of the oil and gas projects is to develop logic models so that the schematic design diagrams for piping and other MEP components are built according to the functional requirements of a facility and without any deviations among the facility elements. The plant life cycle management model used by the oil and gas projects enabled multi-disciplinary teams design simultaneously in a collaboration platform. The oil and gas industry is moving towards design integration. Diagram of engineering design could easily export information to other software and integrate with other engineering design tool (Aveva, 2015a; Aveva, 2015, p. 10-12; Aveva, 2015, p. 13-15; Aveva, 2015, p. 26-30).

Apart from that, the use of 4D modeling for planning, scheduling and sequencing the works in the oil and gas industry is also noticeable. A real-time pipe tracking system which utilised the radio-frequency identification (RFID) and 3D digital models in a handheld mobile device was developed to allow more efficient task management (Kim et al., 2013). Also, a 4D model for scheduling activity and operation of mega LNG construction projects was proposed to improve process planning and control (Zhou et al., 2015a). The engineering data such as the 3D model, piping isometrics and structural steel data were exported to a scheduling tool to create field installation work packages from a virtual construction model (Bentley, 2013, p.62). Another two important functions of BIM are the design review and design authoring which are commonly used in the oil and gas industry. Design review tool was deployed to review the plant design so that installation errors could be reduced (Aveva, 2015a). Design authoring is also used heavily in the oil and gas projects as it is the tool which adds richness of information in the oil and gas facility model. One of the examples is that the tool was used to enable the structure and piping design information to be integrated into the model (Bentley, 2012, p. 105).

Some distinguished DMAT uses which are not commonly used in the built environment include offshore structural analysis; spatial, cable and raceway system analysis; and process analysis. Besides, code checking, design documents and clash detection are the important DMAT uses which are usually embedded into the design software as parts of their supplementary functions. It is important to note that BIM is not about the technology, but it improves project management and collaboration among multi-disciplinary teams. To optimise the functions of the BIM and DMAT such as the clash detection, the regular meeting may be necessary to discuss the collaboration process among different design disciplines.

### 5.3 Procure

Modular construction is very common in the oil and gas projects. Several examples of modularisation strategies for steel designs have been proposed to maximise project savings of the oil and gas projects (Bedair, 2014). It is evident that digital fabrication has become important in the oil and gas industry, particularly in the

steel fabrication components. Corrib onshore gas pipeline project deployed digital fabrication software (Ward et. al., 2014) to provide rapid detailing automation, automatic fabrication shop drawings and computer numeric control (CNC) machinery production deliverables. The software allows effective collaboration between engineers, detailers and fabricators.

Also, the information of plant life cycle model could be exported to into the oil and gas enterprise software for resource management such as the subcontractor and/or supplier management, material management and equipment management. In the BIM context, subcontractor coordination means it is a process of coordination among subcontractor for reviewing the design and optimising the scheduling prior to installations (NATSPEC, 2016). However, this process is not observable neither in the DMAT academic publications nor DMAT vendor case studies. This may due to both sources are technology-oriented, therefore, it is hard to find the discussion on the technology management practices in the oil and gas projects.

In the research and development, a conceptual framework was proposed to assure modular construction quality through introducing a situation awareness construction environment with well-defined sensing and tracking technologies (Chi et. al., 2015). A study investigated the RFID solutions was also conducted to identify the positions of onsite materials and components (Trujens et al., 2014). In practice, various procurement software were adopted in the oil and gas projects such as VPRM procurement and logistics (Aveva, 2015, p.48-51), oracle primavera (Aveva, 2015, p.24-27) and smartplant materials. With the material and supplier/ subcontractor management tool, bills of materials are extracted from the plant design tool to verify its completeness in the tool; supplier past performance can be assessed, new suppliers can be selected based on the selection criteria and maintain their record in the tool; the tool can also allow material status to be tracked, record, updated and activities from inviting subcontractor to manage the sub-contracting are also the functions of the tool (Intergraph, 2013). An integrated supplier management system was set up to include an eSupplier portal, activities from a request for quotation (RFQ)s to award, all post-agreement workflows, and progress control for each subcontract. This allows teams to collaborate more effectively across the engineering, procurement, and construction disciplines (Intergraph

2015). The integrated supplier and subcontractor management were used in Thailand where the procurement office in Bangkok would have to handle suppliers in the Sattahip onshore base to support Bualuang wellhead project (Aveva 2015, p.40-41). 4D modeling and mobile tools were deployed to manage and schedule the equipment for the construction of a new facility to connect to the existing oil and gas facility (Bentley, 2015, p.13).

## 5.4 Construct

Constructability review is important to the design and construction of the oil and gas projects. 4D modeling was used by Abreu e Lima refinery (Synchro, 2015) to analyse the execution and concreting sequence of the ramp and the substation implementation. Wang et al. (2014a) proposed the use of AR and BIM to enable walk-through functionality for facilitating design and constructability review process on the site. Apart from constructability review, the integration of these tools allows on-site progress monitoring to detect real problems, such as low productivity and the tendency of committing an error in assembly. Nevertheless, other BIM uses are not apparent in the oil and gas projects. The BIM use in planning and controlling the construction layout, logistic planning, lift planning and construction system design are not observable in the study. Construction system design is particular significant to the oil and gas projects given the complexity of the design and construction of the facilities. With the adoption of the construction system design, complex facility system such as modular components, formwork and scaffolding can be modeled to improve productivity and safety (NATSPEC, 2016).

Safety element is one of the main concerns of the oil and gas industry. 4D modeling was deployed to sequence the work packages in the NAG Project at the ExxonMobil facility in Texas enabling planning for access and egress routes that contributed to maintaining safety and reducing risk (Bentley, 2015, p.13). The 3D model was also deployed innovatively to review the operational and safety aspects of the surrounding during the design phase (Ward et. al., 2014) and the model could be coupled with various tools such as AR (Albert et.al., 2014; Chen et al., 2015), and hybrid-desk in a semi-immersive environment (Carvalho et al., 2012).

For the completion and commissioning management system (CCMS), the common practices for the built environment sector is the Construction Operations Building Information Exchange (COBie), which is a non-proprietary platform for the exchange of life cycle data needed by facility managers (Kensek, 2015) and it was developed by a number of US public agencies to improve the handover process to building owner-operators (Buxton, 2015). For the oil and gas projects, the industry has their own commissioning system which differs from the building. The facilities and data format involve in the oil and gas projects are large and complex, hence, a real-time tracking system for project commissioning is more appropriate to ensure fast and accurate delivery. The tools carry similar functions of the BIM use such as the field and management tracking and prepare for project completion and commissioning. The examples of common CCMS system used in the oil and gas projects include WinPCS, ContinuumEdge (CE) and qedi.

# 5.5 Production, maintain and operate

Pertaining to the asset management, the oil and gas projects have a more complex facility management system. Enterprise asset management was deployed by the oil and gas exploration and production firm for (1) procurement and materials management; and (2) maintenance planning (Aveva, 2015, p.40-41). It also referred to Computerised Maintenance Management (CMM) system which was used to order materials from anywhere and track the delivery status enabled the operators to take informed actions to reduce the impact on operations. The system could also integrate with another system to ensure the reliable information provided for shutdown maintenance planning or any unplanned downtime. GIS asset tracking was deployed to enable safer and better gas pipeline management in Romania. An integrated 3D map, map server system, pipeline management system and sensors tracking system were established to manage the asset updates (Autodesk, 2012). Another similar system was used to analyse the outage which enabled better customer service (Autodesk, 2012a).

For operation and maintenance training, it is observed that the immersive virtual reality (IVR) which deployed the 3D plant model was proposed to enable the control-room operator (CROP) and field operator (FOP) to be trained

simultaneously. Besides, the IVR enables the performance to be assessed by eliminating the subjectivity and the trainees were trained under an experimental approach instead of classical approach (Colombo et al., 2014). For disaster planning, a 3D visualisation model was integrated with other advanced technologies to monitor and forecast the disaster. By integrating sensor technologies, spatial information technologies, 3D visualisation technologies, and a landslide-forecasting model, it was used to monitor and forecast landslides in the Danjiangkou Reservoir area (Huang et. al., 2016). In the context of BIM, disaster planning is in connection with the BIM use with building management system for emergency response planning (NATSPEC, 2016) which is not apparent in the oil and gas projects. Other BIM uses such as assessment models, space and management tracking, resiliency modeling and logistics management system are not apparent in the oil and gas projects.

Production management is a distinguished DMAT use which is not commonly applied in the built environment. An integrated system which consisted of an upto-date 3D geological model, production management software such as ERP system (Veyber et al., 2012), grid-based production management system (Zhang and Zhang, 2012) was proposed for the upstream oil and gas production management. Information extracted from well data was used to establish cost estimate of drilling and production via Cost Estimate Request (CER) database. The combination of Well Planner and FracScheduler was also proposed to streamline the production scheduling and value stream discipline so as to determine which well is ready for rig work (Allan et al 2014).

# 5.6 Demolition

When the oil and gas field is near the end of its life cycle, it shall prepare for restoring the site to its original condition. The process and production plants would also have to be dismantled. Both the BIM and DMAT uses are not apparent at this stage. The existing conditions modeling and/or deconstruction modeling (Ward et al., 2014) could be used to present the existing as-built model and site conditions to plan for the demolition works. Other DMAT and BIM uses which were used for

planning, designing and construction works could be possibly used in this stage to streamline the demolition process.

# 5.7 Summary

In the planning and design stage, while design reviews, 3D plant modeling, phase planning (4D), design coordination, design documents and code checking become prominent in the oil and gas projects, other BIM uses such as existing conditions modelling, site analysis, cost analysis (5D) and programming for assessing design space can also be deployed to provide more reliable information for the owners, designers and contractors (if they are involved during the early design stage) to make an informed decision on the oil and gas project development. Existing conditions modeling should not only use to model the as-built oil and gas facilities but it should extend to model the surrounding site conditions during the project planning stage and fabricated items before delivering them to a site. During the procure stage, digital fabrication is an essential element to speed up the oil and gas projects while reducing the deviations among the design, fabrications and installations. Subcontractor and supplier management, material and equipment management are also significant to smoothen the procurement process. However, subcontractor coordination is important too to ensure effective model coordination and resolve constructability issues between the different trades. In the construction stage, apart from constructability reviews, progress tracking, safety planning and field and management tracking which are commonly used by the oil and gas projects to improve project performance, other BIM uses such as planning and controlling the construction layout through creation of digital layout; logistic planning which involved detailed logistic objects that linked to construction schedule (4D model); lift planning model that allows the structure engineers and experienced site personnel to communicate the lift plan execution; and construction system design for modeling the complex construction could be implemented to improve the overall productivity of the construction process. In the production, operation and maintenance phase, it is noticed that asset management, GIS asset tracking, operation and maintenance training and production management are usually implemented in the oil and gas projects. Other uses such as assessment models for efficient field data collection; disaster planning for emergency response;

space and management tracking to evaluate, manage and track the existing use space and associated resources within an oil and gas facility; resiliency modelling for the remote areas subject to environmental change; and logistics management system to support entire transportation lifecycle from creating the least cost shipment plans to monitoring the whole distribution network proactively can also be adopted to improve overall operation efficiency. As in the final stage of a project life cycle, existing conditions modeling and de-construction model can be used to plan for the demolition works. Figure 5 shows the potential BIM and DMAT uses for performance improvement in the oil and gas projects.

-Existing Conditions
Modeling
-Site Analysis
-Cost Analysis (5D)
-Programming
-Programming
-Programming
-Construction System
Design

-Existing Conditions
Modeling
-Assessment Models
- Disaster Planning
- Space and Management
- Disaster Planning
- Resiliency Modeling
- Resiliency Modeling
- Existing Conditions
- Assessment Models
- Disaster Planning
- Space and Management
- Tracking
- Resiliency Modeling
- Logistic Management
- System

- Existing Conditions
- Existing Conditions
- Deconstruction
- Disaster Planning
- Construction
- Space and Management
- System
- Syst

Figure 5: Potential BIM and DMAT Uses for the Oil and Gas Projects

### 6. Conclusion and Recommendations

The conducted literature review of twenty-eight (28) BIM guidelines, eighty-three (83) DMAT academic publications and one hundred and one (101) DMAT vendor case studies have streamlined thirty-six (36) BIM and DMAT uses for oil and gas projects. The findings reveal that they are many potential applications of DMAT and BIM uses (figure 5) can be applied in the oil and gas projects for performance improvement. Data and information management system which are commonly implemented in the oil and gas projects could be deployed in the built environment sector to improve the collaboration among multi-disciplinary teams from planning until operation and maintenance phase.

Few limitations need to be considered in this research. This study does not take into account the effective measures of the BIM and DMAT uses. The highlighted

technology practices are only applicable to the technologies, which have a similar taxonomy of (1) DMAT such as the geometry bedding used for oil and gas exploration and production and also PLM system used for design, construction and operation, and (2) BIM. The scope of this study is not extended to the common enterprise computational tools such as the enterprise resource planning (ERP) which is commonly used in the oil and gas firms. Also, the study may overlook some BIM and DMAT uses as per the BIM guidelines, DMAT academic publications and vendor case studies. Future studies may investigate the efficiency use of the BIM and DMAT technologies for the oil and gas project improvement; examine the potential DMAT applications in the built environment sector; and study the technical possibility of linking the PLM, BIM and ERP system for performance improvement in both the oil and gas and built environment sectors.

Acknowledgement

We are grateful to Gary Tan, an IT specialist of oil and gas projects for his time and suggestions of improvement of our paper. This paper was inspired by the preparatory research for the author's PhD project which is co-funded by Curtin University and Australian Research Council (ARC) linkage scholarship #53187.

Compliance with Ethical Standards

**Human Participants Nor Animals** 

The research does not involve neither human participants nor animals

**Informed Consent** 

All the authors are informed and provided their consent.

Conflict of Interest

The authors declare that they have no conflict of interest.

References

34

- Abdideh, M. and Bargahi, D., 2012. Designing a 3D model for the prediction of the top of formation in oil fields using geostatistical methods. Geocarto International, 27(7), pp.569-579.
- AEC UK, 2015. AEC (UK) BIM Protocol, London, UK.
- AGC, 2009. The Contractor's Guide to BIM, Associated General Contractors of America, Virginia, USA.
- Albert, A., Hallowell, M.R., Kleiner, B., Chen, A. and Golparvar-Fard, M., 2014. Enhancing construction hazard recognition with high-fidelity augmented virtuality. Journal of Construction Engineering and Management, 140(7), p.04014024.
- Allan, M.E., Reese, D.W. and Gold, D.K., 2014, April. Application of Toyota's Principles and Lean Processes to Reservoir Management: More Tools to Overload the Toolbox or a Step Change in Our Business?. In SPE Western Regional & AAPG Pacific Section Meeting 2013 Joint Technical Conference. Society of Petroleum Engineers.
- Amanipoor, H., Ghafoori, M. and Lashkaripour, G.R., 2013. The application of géostatistical methods to prepare the 3D petrophysical model of oil reservoir. Open Journal of Geology, 3, 7-18
- Amoyedo, S.O., Ekut, E., Salami, R., Goncalves-Ferreira, L. and Desegaulx, P., 2014, October. Time Lapse (4D) Seismic for Reservoir Management: Case Studies from Offshore Niger Delta, Nigeria. In SPE Annual Technical Conference and Exhibition. Society of Petroleum Engineers.
- Ask, M.V., Ask, D., Elvebakk, H. and Olesen, O., 2015. Stress Analysis in Boreholes Drag Bh and Leknes Bh, Nordland, North Norway. Rock Mechanics and Rock Engineering, 48(4), pp.1475-1484.
- Aspentech, 2015. Global Refiner Deploys Cost Estimation Solution to Accelerate Decision Making and Lower Costs. Aspen Technology, Burlington, Massachusetts, United States
- Aspentech, 2015a. Process Ecology Reduces Capital Costs and Prevents Downtime by Using Aspen HYSYS® Family. Aspen Technology, Burlington, Massachusetts, United States

- Aspentech, 2015b. EPC Leader Adopts Integrated Engineering Solution to Drive Growth in FEED Business. Aspen Technology, Burlington, Massachusetts, United States
- Aspentech, 2016. Gas-to-Liquid Technology Provider Scales-up and Optimizes Plant Design Using the aspenONE® Engineering Suite, Aspen Technology, Burlington, Massachusetts, United States.
- Autodesk, 2012. A new way of working: GDF SUEZ Energy Romania Customer Success Story. Autodesk, USA.
- Autodesk, 2012a. Connecting the enterprise: Okaloosa Gas District Customer Success Story. Autodesk, USA.
- Autodesk, 2013. Dynamic design drives dynamic growth: Civil & Environmental Consultants, Inc. (CEC), Autodesk, USA.
- Autodesk, 2013a. Weeks of Work Reduced to Minutes. NATCO Group, Inc. Customer Success Story, Autodesk, USA.
- Aveva, 2012. AVEVA releases Structural Analysis Interface SP for STAAD.Pro.

  23 August, Press release. AVEVA. Retrieved from :
  http://www.aveva.com/en/News-Events/Press-Releases/Press-Releases2012/Corporate/AVEVA\_releases\_SAI-SP.aspx [ 15 June 2016]
- Aveva, 2015. AVEVA World Focus. Oil & Gas Projects, innovation and experiences from past issues of AVEVA World Magazine. Aveva, Cambridge, UK.
- Aveva, 2015a. AVEVA E3D increases profitability and competitiveness at Tekfen Engineering, Turkey's largest engineering company: Aveva Case study, Cambridge, UK.
- Aveva, 2015b. Information Management Delivers Clear Benefits for Petroleum Development Oman: Aveva Case Study. Aveva, Cambridge, UK.
- Aveva, 2015c. AVEVA Engineering enables six-fold growth at Giprogazoochistka. Aveva, Cambridge, UK.
- Aveva, 2015d. Integrated Engineering and Design: An AVEVA solution for capital and brownfield projects. Aveva Group plc, Cambridge, UK.
- Azhar, S., 2011. Building information modeling (BIM): Trends, benefits, risks, and challenges for the AEC industry. Leadership and Management in Engineering, 11(3), pp.241-252.

- Baaziz, A. and Quoniam, L., 2013. How to use Big Data technologies to optimize operations in Upstream Petroleum Industry. Baaziz, A., & Quoniam, L. (2013). How to use Big Data technologies to optimize operations in Upstream Petroleum Industry. International Journal of Innovation-IJI, 1(1), pp.19-25.
- BCA, 2013. Singapore BIM Guide, Building and Construction Authority: Singapore.
- Beck, R., 2011. Improve decision-making for LNG projects via an integrated technology: This approach to modeling and economics cuts through the complexity of project capital investment. Hydrocarbon processing, 90(7), pp.51-54.
- Bedair, O., 2014. Cost effective modularization strategies for industrial facilities used in mega Oil & gas projects. Recent Patents on Engineering, 8(2), pp.120-132.
- Beeson, D., Hoffman, K., Larue, D., McNaboe, J. and Singer, J., 2014. Creation and utility of a large fit-for-purpose earth model in a giant mature field: Kern River field, California. AAPG Bulletin, 98(7), pp.1305-1324.
- Bentley, 2012. The Year in Infrastructure. Bentley Systems, Incorporated. Exton, Pennsylvania, USA.
- Bentley, 2013. The Year in Infrastructure. Bentley Systems, Incorporated. Exton, Pennsylvania, USA.
- Bentley, 2014. The Year in Infrastructure. Bentley Systems, Incorporated. Exton, Pennsylvania, USA.
- Bentley, 2015. The Year in Infrastructure. Bentley Systems, Incorporated. Exton, Pennsylvania, USA.
- BHP, 2015. Speaking Oil and Gas. BHP Biliton Petroleum Pty Ltd, Australia.
- Brigaud, B., Vincent, B., Durlet, C., Deconinck, J.F., Jobard, E., Pickard, N., Yven, B. and Landrein, P., 2014. Characterization and origin of permeability–porosity heterogeneity in shallow-marine carbonates: From core scale to 3D reservoir dimension (Middle Jurassic, Paris Basin, France). Marine and Petroleum Geology, 57, pp.631-651.
- Bruns, B., Di Primio, R., Berner, U. and Littke, R., 2013. Petroleum system evolution in the inverted Lower Saxony Basin, northwest Germany: a 3D basin modeling study. Geofluids, 13(2), pp.246-271.

- Buxton, P. ed., 2015. Metric Handbook: Planning and Design Data. Routledge.5th Ed. Routledge, New York.
- Cacace, M. and Blöcher, G., 2015. MeshIt—a software for three dimensional volumetric meshing of complex faulted reservoirs. Environmental Earth Sciences, 74(6), pp.5191-5209.
- Carvalho, F.G., Trevisan, D.G. and Raposo, A., 2012. Toward the design of transitional interfaces: an exploratory study on a semi-immersive hybrid user interface. Virtual Reality, 16(4), pp.271-288.
- CFM, 2010. The VA BIM Guide, Department of Veterans Affairs, Construction & Facilities Management, Washington DC, USA.
- Chelmis, C., Zhao, J., Sorathia, V.S., Suchindra, A. and Prasanna, V.K., 2013. Toward an Automatic Metadata Management Framework for Smart Oil Fields. SPE Economics & Management, 5(01), pp.33-43.
- Chemali, R., Semac, W., Balliet, R., Cooper, P., Torres, D. and Jones, C., 2014. Formation-Evaluation Challenges and Opportunities in Deepwater. Petrophysics, 55(02), pp.124-135.
- Chen, Y.C., Chi, H.L., Kang, S.C. and Hsieh, S.H., 2015. Attention-Based User Interface Design for a Tele-Operated Crane. Journal of Computing in Civil Engineering, 30(3), p.04015030.
- Chi, H.L., Wang, J., Wang, X., Truijens, M. and Yung, P., 2015. A conceptual framework of quality-assured fabrication, delivery and installation processes for liquefied natural gas (LNG) plant construction. Journal of Intelligent & Robotic Systems, 79(3-4), pp.433-448.
- Chong, H.Y., Lopez, R., Wang, J., Wang, X. and Zhao, Z., 2016. Comparative Analysis on the Adoption and Use of BIM in Road Infrastructure Projects. *Journal of Management in Engineering*, p.05016021.
- Chong, H.Y. and Wang, X., 2016a. The outlook of building information modeling for sustainable development. Clean Technologies and Environmental Policy, pp.1-11.
- COD, 2011. BIM GUIDE, College of the Desert, Palm Desert, USA.
- Colombo, S., Nazir, S. and Manca, D., 2014. Immersive Virtual Reality for Training and Decision Making: Preliminary Results of Experiments Performed With a Plant Simulator. SPE Economics & Management, 6(04), pp.165-172.

- COSA, 2011. Building Information Modeling (BIM) Development Criteria and Standards for Design & Construction Projects. COSA BIM Standards. City of San Antonio, City of San Antonio, Texas.
- CRC, 2009. Naational Guidelines for Digital Modeling, CRC Construction Innovation, Queensland, Australia.
- Credit Suisse, 2014. Quarterly Brazil tracker, Equity Research, Integrated Oil and Gas, 20 January, Credit Suisse Securities Research and Analystics.
- Cuba, P.H., Miskimins, J.L., Anderson, D.S. and Carr, M., 2012, January.Impacts of Diverse Fluvial Depositional Environments on Hydraulic Fracture Growth in Tight Gas Reservoirs. In SPE Hydraulic Fracturing Technology Conference. Society of Petroleum Engineers.
- Darko, E., 2014. Short guide summarising the oil and gas industry lifecycle for a non-technical audience. Overseas Development Institute, London, UK.
- de Oliveira Miranda, A.C., Lira, W.W.M., Marques, R.C., Pereira, A.M.B., Cavalcante-Neto, J.B. and Martha, L.F., 2015. Finite element mesh generation for subsurface simulation models. Engineering with Computers, 31(2), pp.305-324.
- Do Couto, D., Gumiaux, C., Jolivet, L., Augier, R., Lebret, N., Folcher, N., Jouannic, G., Suc, J.P. and Gorini, C., 2015. 3D modelling of the Sorbas Basin (Spain): new constraints on the Messinian Erosional Surface morphology. Marine and Petroleum Geology, 66, pp.101-116.
- DOA/DSF, 2012. BIM Guidelines & Standards for ARCHITECTS and ENGINEERS Department of Administration, Division of State Facilities, Wisconsin, USA
- Dong, T., He, S., Wang, D. and Hou, Y., 2014. Hydrocarbon migration and accumulation in the Upper Cretaceous Qingshankou Formation, Changling Sag, southern Songliao Basin: Insights from integrated analyses of fluid inclusion, oil source correlation and basin modelling. Journal of Asian Earth Sciences, 90, pp.77-87.
- Downton, G., 2015. Systems Modeling and Design of Automated-Directional-Drilling Systems. SPE Drilling & Completion, 30(03), pp.212-232.
- Duran, E.R., di Primio, R., Anka, Z., Stoddart, D. and Horsfield, B., 2013. 3D-basin modelling of the Hammerfest Basin (southwestern Barents Sea): A

- quantitative assessment of petroleum generation, migration and leakage. Marine and petroleum geology, 45, pp.281-303.
- EY, 2014. Spotlight on oil and gas megaprojects. Ernst and Young Global Limited, London, UK.
- Fayemi, O. and Di, Q., 2016. 2D Multitransient Electromagnetic Response Modeling of South China Shale Gas Earth Model Using an Approximation of Finite Difference Time Domain with Uniaxial Perfectly Matched Layer. Discrete Dynamics in Nature and Society, 2016.
- Fegh, A., Riahi, M.A. and Norouzi, G.H., 2013. Permeability prediction and construction of 3D geological model: application of neural networks and stochastic approaches in an Iranian gas reservoir. Neural Computing and Applications, 23(6), pp.1763-1770.
- FMS, 2012. BIM Guidelines, University of Southern California Facilities Management Services, Los Angeles, USA.
- Geiger, S., Lord, G. and Tambue, A., 2012. Exponential time integrators for stochastic partial differential equations in 3D reservoir simulation. Computational Geosciences, 16(2), pp.323-334.
- Glegola, M.A., Ditmar, P., Hanea, R., Eiken, O., Vossepoel, F.C., Arts, R. and Klees, R., 2012. History Matching Time-Lapse Surface-Gravity and Well-Pressure Data With Ensemble Smoother for Estimating Gasfield Aquifer Support--A 3D Numerical Study. SPE Journal, 17(04), pp.966-980.
- Gourlis, G. and Kovacic, I., 2016. Building Information Modelling for analysis of energy efficient industrial buildings—A case study. Renewable and Sustainable Energy Reviews.
- GSA, 2015. National 3D-4D BIM Program, United States General Services Administration, Washington, USA.
- GSFIC, 2013. BIM Guide, Georgia State Financing and Investment Commission, Georgia, USA.
- GTFM, 2016. Georgia Tech BIM Requirements & Guidelines for Architects, Engineers and Contractors, Georgia Tech Facilities Management, Georgia, USA.
- Han, M.K., Kim, W.K. and Park, M.G., 2014. Development of a Collaboration System based on Mobile Framework in the Field of Ships and Marine

- Industry. International Journal of Multimedia and Ubiquitous Engineering, 9(4), pp.121-126.
- Harvard, 2016. BIM Uses Guide, Harvard University Construction Management Council, Cambridge, USA.
- He, W. and Wang, F.K., 2015. A Hybrid Cloud Model for Cloud Adoption by Multinational Enterprises. Journal of Global Information Management (JGIM), 23(1), pp.1-23.
- HKCIC, 2015. CIC Building Information Modelling Standards (Phase One). Construction Industry Council, Wanchai, Hong Kong.
- HM Government, 2013. Building Information Modeling. Industrial strategy: government and industry in partnership, Construction 2025, July 2013. London, UK.
- Hu, G., Campbell, M. and Huang, C., 2014. Dynamic Plastic Deformation of Deepwater Steel Catenary Risers Under Extreme Cyclic Compressive Loading. Oil and Gas Facilities, 4(01), pp.73-79.
- Huang, H., Ni, J., Zhang, Y., Qian, T., Shen, D. and Wang, J., 2016. Web3DGIS-Based System for Reservoir Landslide Monitoring and Early Warning. Applied Sciences, 6(2), p.44.
- Infrastructure Australia, 2016. Australian Infrastructure Plan. Priorities and reforms for our nation's future, New South Wales, Australia.
- Intergraph 2015a. Case Study: Eco Fox, Italy. Madison, Alabama, United States.
- Intergraph 2015a. Case Study: Vietsovpetro, Vietnam. Madison, Alabama, United States.
- Intergraph, 2012. Case study: China National Offshore Oil Corporation, China. Intergraph Corporation. Madison, Alabama, United States.
- Intergraph, 2013. Case study: OHL Industrial, Spain. Intergraph Corporation. Madison, Alabama, United States.
- Intergraph, 2013a. Case Study: Gasco, United Arab Emirates. Madison, Alabama, United States.
- Intergraph, 2014. Case study: On Line Design & Engineering Ltd., England. Madison, Alabama, United States.
- Intergraph, 2014a. Case Study: Nortech, United Kingdom. Madison, Alabama, United States.

- Intergraph, 2015. Case Study: Leighton Uses SmartPlant® Materials to Assist in Securing New Contract on LNG Megaproject. Madison, Alabama, United States.
- Intergraph, 2016. Grenland Group, Norway. Madison, Alabama, United States.
- Intergraph, 2016a. Intergraph Aids Remote Engineering for Delta Hudson. Madison, Alabama, United States.
- Intergraph, 2016b.ABB, Italy. Madison, Alabama, United States.
- IU, 2015. BIM Guidelines & Standards for Architects, Engineers, and Contractors.
  Indiana University, Indiana, United States.
- Iversen, F., Gressgård, L.J., Thorogood, J., Balov, M.K. and Hepso, V., 2013. Drilling Automation: Potential for Human Error. SPE Drilling & Completion, 28(01), pp.45-59.
- Jain, R., Syal, S., Long, T.A., Wattenbarger, R.C. and Kosik, I.J., 2013. An integrated approach to design completions for horizontal wells for unconventional reservoirs. SPE Journal, 18(06), pp.1-026.
- Kamali, M.R., Omidvar, A. and Kazemzadeh, E., 2013. 3D Geostatistical Modeling and Uncertainty Analysis in a Carbonate Reservoir, SW Iran. Journal of Geological Research, 2013.
- Katterbauer, K., Hoteit, I. and Sun, S., 2015. History Matching of Electromagnetically Heated Reservoirs Incorporating Full-Wavefield Seismic and Electromagnetic imaging. SPE Journal.
- Kensek, K., 2015. BIM Guidelines Inform Facilities Management Databases: A Case Study over Time. Buildings, 5(3), pp.899-916.
- Kim, C.H., Kwon, S.W. and Cho, C.Y., 2013. Development of automated pipe spool monitoring system using RFID and 3D model for plant construction project. KSCE Journal of Civil Engineering, 17(5), pp.865-876.
- Kim, J.D., Choi, S.B., Lee, J.M., Kim, M.K., Choi, S.C., Hwang, I.J. and Choi, J.B., 2014. Conceptual design of a web-based LNG plant management system through adoption of the integrated environment for design and maintenance. Journal of Mechanical Science and Technology, 28(9), pp.3759-3767.
- King, M.J., Ballin, P.R., Bennis, C., Heath, D.E., Hiebert, A.D., McKenzie, W., Rainaud, J.F. and Schey, J., 2012. Reservoir modeling: From rescue to resqml. SPE Reservoir Evaluation & Engineering, 15(02), pp.127-138.

- Kulga, K.S. and Menshikov, P.V., 2015. Computer-Aided Design of Layouts for Cutting Shells for Chemical and Oil-and-Gas Engineering Articles. Chemical and Petroleum Engineering, 51(7-8), pp.540-547.
- Kvesić, M., Reimer, U., Froning, D., Lüke, L., Lehnert, W. and Stolten, D., 2012. 3D modeling of an HT-PEFC stack using reformate gas. International Journal of Hydrogen Energy, 37(17), pp.12438-12450.
- LACCD, 2016. BIM Standard. Los Angeles Community College District, Los Angeles, USA.
- Landmark, 2012. Real-Time Surveillance Optimizes Production at Black Hills E&P. Halliburton, Houston, USA.
- Landmark, 2016. Collaborative Well Solution Reduces Offshore Rig Time by 15 Days for NOC Off South America. Halliburton, Houston, USA.
- Lee, D.Y., Chi, H.L., Wang, J., Wang, X. and Park, C.S., 2016. A linked data system framework for sharing construction defect information using ontologies and BIM environments. *Automation in Construction*, 68, pp.102-113.
- Li, H.Y., Chen, Y. and Zhao, D., 2013. The Design and Implementation of 3D Visualization Pipeline Information System Based on 2D Figures. In Applied Mechanics and Materials (Vol. 246, pp. 1241-1245). Trans Tech Publications.
- Lindsay, M.D., Jessell, M.W., Ailleres, L., Perrouty, S., de Kemp, E. and Betts, P.G., 2013. Geodiversity: exploration of 3D geological model space. Tectonophysics, 594, pp.27-37.
- Liu, J., Huang, X., Wu, C., Cheng, W., Xiang, W. and Xia, H., 2012. From the area to the point-study on the key technology of 3D geological hazard modeling in Three Gorges Reservoir area. Journal of Earth Science, 23, pp.199-206.
- Ma, J.Y., 2014. Fast Production Recovery of a Typhoon-Damaged Oil Field in the South China Sea. Oil and Gas Facilities, 3(05), pp.66-71.
- Marongiu-Porcu, A., Zhang, K., Gakhar, K., Porcu, M.M., Lee, D., Shan, D.,
  Malpani, R., Pope, T., Sobernheim, D. and Acock, A., 2016, February.
  Advanced Modeling of Interwell Fracturing Interference: An Eagle Ford
  Shale Oil Study-Refracturing. In SPE Hydraulic Fracturing Technology
  Conference. Society of Petroleum Engineers.
- MPA, 2015. Appendix A: MPA BIM Guidelines. Massachusets Port Authority, Boston, USA.

- Muley, P., Kulkarni, S., Kurhekar, R. and Thorat, S., 2014. 3D Virtual Glove for Data Logging and Pick and Place Robot. IJECCE, 5(2), pp.319-324.
- Munoz-Garcia, E., 2014. Risk-Based Passive Fire-Protection Optimization. Oil and Gas Facilities, 3(01), pp.67-75.
- Naji, H.S., Khalil, M.K., 2012. 3D geomodeling of the Lower Cretaceous oil reservoir, Masila oil field, Yemen. Arab J Geosci, 5:723–746.
- National BIM Standard, 2015. National BIM Standard-United States® (NBIMS-USTM) Version 3, Washington, USA.
- National BIM Standard, 2015. Practice Dcuments: The Uses of BIM. National BIM Standard United States® Version 3, Washington, USA.
- NATSPEC, 2016. NATSPEC National BIM Guide. NATSPEC Construction Information, Sydney, Australia.
- NHBA, 2012. BoligBIM (BIM Manual), Boligprodusentene (Norwegian Home Builders Association), Oslo, Norway.
- Nikolaou, M., 2013. Computer-aided process engineering in oil and gas production. Computers & Chemical Engineering, 51, pp.96-101.
- Norden, B., Förster, A., Behrends, K., Krause, K., Stecken, L. and Meyer, R., 2012. Geological 3-D model of the larger Altensalzwedel area, Germany, for temperature prognosis and reservoir simulation. Environmental Earth Sciences, 67(2), pp.511-526.
- Norton, K.D., Saura, M.B. and Scholtz, C.R., 2014. Safety management systems at unregulated upstream oil and gas facilities. Process Safety Progress, 33(3), pp.259-264.
- NRC, 2014. National BIM Guidelines and Case Studies for Infrastructure. Sustainable Built Environment National Research Centre, Perth, Australia.
- NYCDDC, 2012. BIM Guidelines. Department Design and Construction, New York, United States.
- NYCSCA, 2014. BIM Guidelines and Standards for Architects and Engineers, New York City School Construction Authority, New York, USA.
- OFCC, 2012.BIM Protocol, State of Ohio Facilities Construction Commission, Ohio, USA.
- Panfili, P., Cominelli, A., Calabrese, M., Albertini, C., Savitsky, A. and Leoni, G., 2012. Advanced upscaling for kashagan reservoir modeling. SPE Reservoir Evaluation & Engineering, 15(02), pp.150-164.

- Paradigm, 2013. Paradigm plays an essential role in the GNS SCIENCE 4D-Taranaki project.PESA News Resources, April/May, 2013, Perth, WA.
- Paradigm, 2016.EarthStudy 360 Delivers New Information about Fractures in Carbonate Reservoirs. Paradigm, Houston, USA.
- Paradigm, 2016a. Generating a Full Field Development Plan in a Highly Restricted Urban Drilling Location. Paradigm, Houston, USA.
- Paradigm, 2016b.Paradigm SKUA Delivers a Full Static Model in a Highly Complex Structural Environment. Paradigm, Houston, USA.
- Paradigm, 2016c.Combining Geostatistics with Seismic Attributes to Improve Reservoir Management Strategies: A Case Study from the Orinoco Petroleum Belt. Paradigm, Houston, USA.
- Paris, L. and Cahay, M., 2014, May. Challenges in a Multi-Disciplinary Approach for Explosion Design of FLNG. In Offshore Technology Conference.

  Offshore Technology Conference.
- Park, H.Y. and Datta-Gupta, A., 2013. Reservoir management using streamline-based flood efficiency maps and application to rate optimization. Journal of Petroleum Science and Engineering, 109, pp.312-326.
- Pathak, P.D., Kocurek, C.G. and Taylor, S.L., 2013. Design Method Combing API and ASME Codes for Subsea Equipment for HPHT Conditions Up to 25,000 psi Working Pressure and Temperature to 400 F.Offshore Technology Conference, Houston, 6-9 May.
- Perrons, R.K. and Hems, A., 2013. Cloud computing in the upstream oil & gas industry: A proposed way forward. Energy Policy, 56, pp.732-737.
- Perrons, R.K. and Jensen, J.W., 2015. Data as an asset: What the oil and gas sector can learn from other industries about "Big Data". Energy Policy, 81, pp.117-121.
- Perrons, R.K. and Richards, M.G., 2013. Applying maintenance strategies from the space and satellite sector to the upstream oil and gas industry: A research agenda. Energy Policy, 61, pp.60-64.
- Petex, 2014. Multi Well Allocation Using Digital Oilfield (DOF) Technology in the Norwegian Sea. Petroleum Experts, 2(1), Houston, USA.
- Popa, A. and Cassidy, S., 2012. i-field Programs Enable Operational Excellence in a Challenging Environment--Pushing the Limits of Large Data Transfer for

- Real-Time Monitoring and Surveillance Operations in San Joaquin Valley. SPE Economics & Management, 4(02), pp.83-89.
- PSU, 2011. BIM Execution Planing: BIM Uses. Penn State University, University Park, PA, USA.
- Reid, S., Cann, G., 2016. The good, the bad and the ugly: The changing face of Australia's LNG production. Deloitte, Canberra, Australia.
- Savazzi, S., Guardiano, S. and Spagnolini, U., 2013. Wireless sensor network modeling and deployment challenges in oil and gas refinery plants. International Journal of Distributed Sensor Networks, 2013.
- Sawaryn, S.J., Pirie, L., Green, I., Scott, A., Cosgrove, B. and Emslie, I., 2014. Integration and assurance of well documents and data—Essential preparation for tomorrow. SPE Economics & Management, 6(01), pp.3-14.
- Schlumberger, 2012. Case study: Geomechanics and Drilling optimization Workflows improve horizontal Well Campaigns in Peru. Schlumberger, Houston, Texas, United States.
- Schlumberger, 2013. Case study: Collaborative Visualization Environment Enhances Exploration at PetroSA. Schlumberger, Houston, Texas, United States.
- Schlumberger, 2013a. Case study: AGIBA Optimises Drilling with Real-time Data. Schlumberger, Houston, Texas, United States.
- Schlumberger, 2013b. Case study: Hidden Fault detection in haynesville Shale Prevents loss of 33% Gas Production. Schlumberger, Houston, Texas, United States.
- Schlumberger, 2014. Case Study: 3D Geological Model Based on Sequence Stratigraphy Reduces Uncertainty in Deep Carbonate Reservoirs. Schlumberger, Houston, Texas, United States.
- Schlumberger, 2014a. Case Study: GDF Suez Defines Key Drilling Investments with Collaborative Well Planning. Schlumberger, Houston, Texas, United States.
- Schlumberger, 2015. Case Study: RWE Dea Streamlines Asset Data Management with eSearch Software Implementation. Schlumberger, Houston, Texas, United States.

- Schlumberger, 2015a. Case Study: Oil India Identifies Deep Exploration Targets Using Petrel Platform's Integration of Seismic and Well Data. Schlumberger, Houston, Texas, United States.
- Schlumberger, 2015b. Case Study:Eni Deploys High Resolution Reservoir Simulator Across Complex Global Assets. Schlumberger, Houston, Texas, United States.
- Schlumberger, 2016. Case Study: While Drilling Formation Evaluation and Interpretation Guides Geosteering to Target Zones, North Sea. Schlumberger, Houston, Texas, United States.
- Schlumberger, 2016a. Case Study:Rashpetco Extends Development Plan by Updating Model in the Petrel Platform, Offshore Egypt. Schlumberger, Houston, Texas, United States.
- Schlumberger, 2016b. Case Study:Petrel Platform Enables High-Resolution, Quantitative Modeling of Complex, Heterogeneous Reservoir. Schlumberger, Houston, Texas, United States.
- SDCCD, 2012. BIM Standards for Architects, Engineers & Contractors, San Diego Community College District, San Diego, USA.
- SEC, 2013. First Steps to BIM Competence: A Guide for Specialist Contractors, Specialist Engineering Contractors' Group and BIM Academy at the University of Northumbria, Northumbria, UK.
- Senel, O., Will, R. and Butsch, R.J., 2014. Integrated reservoir modeling at the Illinois Basin–Decatur Project. Greenhouse Gases: Science and Technology, 4(5), pp.662-684.
- Shou, W., Wang, J., Wang, X. and Chong, H.Y., 2015. A comparative review of building information modelling implementation in building and infrastructure industries. *Archives of computational methods in engineering*, 22(2), pp.291-308.
- Soleimani, M. and Shokri, B.J., 2015. 3D static reservoir modeling by geostatistical techniques used for reservoir characterization and data integration. Environmental Earth Sciences, 74(2), pp.1403-1414.
- Statsbygg, 2012. Statsbygg BIM Manual, Statsbygg, Oslo, Norway.
- Synchro 2014. Using Synchro in the life cycle of an EPC project. Case: TECAB (Expansion of the ground Terminal Cabiúnas ) for Petrobras S/A. Consórcio SPS, São Carlos, Brazil.

- Synchro 2015. Systems Development: Planning and BIM.Construções e Comércio Camargo Correa S.A., Brazil.
- Tavallali, M.S. and Karimi, I.A., 2015. Integrated Oil Field Management–from Well Placement and Planning to Production Scheduling. Industrial & Engineering Chemistry Research.
- Tekla, 2016. Saipem Offshore. Trimble Solutions Corporation, Espoo. Finland.
- Tekla, 2016a. Neste Oil Diesel production line. Trimble Solutions Corporation, Espoo. Finland.
- Tekla, 2016b. Offshore Structures. Trimble Solutions Corporation, Espoo. Finland.
- Tekla, 2016c. Lamprell. Trimble Solutions Corporation, Espoo. Finland.
- Teo, E. A. L., Ofori, G, Tjandra, I K and Kim, H, 2015. The potential of Building Information Modelling (BIM) for improving productivity in Singapore construction In: Raidén, A B and Aboagye Nimo, E (Eds) Procs 3 st Annual ARCOM Conference, 7-9 September 2015, Lincoln, UK, Association of Researchers in Construction Management, 661-670.
- Tiruneh, H.W., Stetler, L.D., Oberling, Z.A., Morrison, D.R., Connolly, J.L. and Ryan, T.M., 2013, January. Discontinuity mapping using Ground-Based LiDAR: Case study from an open pit mine. In 47th US Rock Mechanics/Geomechanics Symposium. American Rock Mechanics Association.
- TPA, 2015. E/A Design Division BIM Standard. The Port Authority of NY & NJ Engineering Department, New York, United States.
- Truijens, M., Wang, X., de Graaf, H. and Liu, J.J., 2014. Evaluating the performance of absolute rssi positioning algorithm-based microzoning and rfid in construction materials tracking. Mathematical Problems in Engineering, 2014.
- Turrini, C., Lacombe, O. and Roure, F., 2014. Present-day 3D structural model of the Po Valley basin, Northern Italy. Marine and Petroleum Geology, 56, pp.266-289.
- USACE, 2012. Roadmap for Life-Cycle BIM, United States Army Corps of Engineers, Washington DC, USA.
- Veyber, V., Kudinov, A. and Markov, N., 2012. Model-driven platform for oil and gas enterprise data integration. International Journal of Computer Applications, 49(5).

- Walnum, H.T., Nekså, P., Nord, L.O. and Andresen, T., 2013. Modelling and simulation of CO 2 (carbon dioxide) bottoming cycles for offshore oil and gas installations at design and off-design conditions. Energy, 59, pp.513-520.
- Wang, J., Wang, X., Shou, W. and Xu, B., 2014. Integrating BIM and augmented reality for interactive architectural visualisation. *Construction Innovation*, 14(4), pp.453-476.
- Wang, X., Yung, P., Luo, H. and Truijens, M., 2014a. An innovative method for project control in LNG project through 5D CAD: A case study. Automation in Construction, 45, pp.126-135.
- Wang, X., Truijens, M., Hou, L., Wang, Y. and Zhou, Y., 2014b. Integrating Augmented Reality with Building Information Modeling: Onsite construction process controlling for liquefied natural gas industry. Automation in Construction, 40, pp.96-105.
- Wang, J., Zhang, X., Shou, W., Wang, X., Xu, B., Kim, M.J. and Wu, P., 2015. A BIM-based approach for automated tower crane layout planning. *Automation in Construction*, 59, pp.168-178.
- Wang, J., Sun, W., Shou, W., Wang, X., Wu, C., Chong, H.Y., Liu, Y. and Sun, C., 2015. Integrating BIM and LiDAR for real-time construction quality control. *Journal of Intelligent & Robotic Systems*, 79(3-4), pp.417-432.
- Wang, J., Wang, X., Shou, W., Chong, H.Y. and Guo, J., 2016. Building information modeling-based integration of MEP layout designs and constructability. *Automation in Construction*, *61*, pp.134-146.
- Wang, J., Shou, W., Wang, X. and Wu, P., 2016. Developing and evaluating a framework of total constraint management for improving workflow in liquefied natural gas construction. *Construction Management and Economics*, pp.1-16.
- Ward, D., Butler, C., Khan, S. and Coyle, B., 2014, August. Corrib onshore gas pipeline, Ireland–using BIM on a large infrastructure project. In Proceedings of the Institution of Civil Engineers-Civil Engineering (Vol. 167, No. 3, pp. 123-130). Thomas Telford Ltd.
- WinPCS, 2014a. North Rankin Redevelopment Project Setting new benchmarks for integrating offshore greenfield and brownfield production facilities, Complan.
- WinPCS, 2014b. Jansz-Io Subsea Pipeline Scarp Crossing, Complan.

- WinPCS, 2014c. PNG LNG Project starts first production ahead of schedule, Complan.
- Xie, Y. and Ma, Y., 2015. Design of a multi-disciplinary and feature-based collaborative environment for chemical process projects. Expert Systems with Applications, 42(8), pp.4149-4166.
- Xu, X.H., Peng, G., Liu, X.F., and S.Y.L., 2012, August. Oil and Gas Exploration Information Integration Management Plan Based on GIS Technology. In Computational and Information Sciences (ICCIS), 2012 Fourth International Conference on (pp. 526-529). IEEE.
- Xue, C., 2015. Technology Integration Capability in the Oil/Gas Industry: Cross case study of iRing and BIM (Doctoral dissertation, TU Delft, Delft University of Technology).
- Zeinalzadeh, A., Moussavi-Harami, R., Mahboubi, A. and Sajjadian, V.A., 2015. Basin and petroleum system modeling of the Cretaceous and Jurassic source rocks of the gas and oil reservoirs in Darquain field, south west Iran. Journal of Natural Gas Science and Engineering, 26, pp.419-426.
- Zhang, X.W.and Zhang, J., 2012. Research on the Grid-based Production Management System for Digital Oil Field. International Journal of Digital Content Technology & its Applications, 6(8), pp.80-88.
- Zhou, J., Love, P.E.D., Matthews, J., Carey, B. and Sing, C.P., 2015. Object-oriented model for life cycle management of electrical instrumentation control projects. Automation in Construction, 49, pp.142-151.
- Zhou, Y., Ding, L., Wang, X., Truijens, M. and Luo, H., 2015a. Applicability of 4D modeling for resource allocation in mega liquefied natural gas plant construction. Automation in Construction, 50, pp.50-63.
- Zhu, L., Liu, X., He, S., Shi, J. and Pang, M., 2015. Keywords co-occurrence mapping knowledge domain research base on the theory of Big Data in oil and gas industry. Scientometrics, 105(1), pp.249-260.
- Zhu, L.F., Li, M.J., Li, C.L., Shang, J.G., Chen, G.L., Zhang, B. and Wang, X.F., 2013. Coupled modeling between geological structure fields and property parameter fields in 3D engineering geological space. Engineering Geology, 167, pp.105-116.

Zhu, L.F., Wang, X.F. and Zhang, B., 2014. Modeling and visualizing borehole information on virtual globes using KML. Computers & Geosciences, 62, pp.62-70.